Development Services

From Concept to Construction

Phone: 503-823-7300 Email: bds@portlandoregon.gov 1900 SW 4th Ave, Portland, OR 97201

More Contact Info (http://www.portlandoregon.gov//bds/article/519984)



APPEAL SUMMARY

Status: Decision Rendered - Held over from ID 27898 (7/27/22) for additional information

Appeal ID: 27926	Project Address: 12005 N Burgard Rd
Hearing Date: 8/3/22	Appellant Name: Joshua W Christiansen
Case No. : B-009	Appellant Phone: 5036438595
Appeal Type: Building	Plans Examiner/Inspector: Steven Mortensen
Project Type: commercial	Stories: 1 Occupancy: F-1 Construction Type: II-B
Building/Business Name: Shredder Enclosure	Fire Sprinklers: No
Appeal Involves: Reconsideration of appeal	LUR or Permit Application No.: 22-104962-CO
Plan Submitted Option: pdf [File 1] [File 2]	Proposed use: Enclosure of Existing Equipment

APPEAL INFORMATION SHEET

Appeal item 1

Code Section	OSSC Table 2902.1
Requires	Plumbing fixtures shall be provided in the minimum number as shown in Table 2902.1 based on the actual use of the building or space.
Code Modification or Alternate Requested	Requesting an exemption to not provide a bathroom for this equipment enclosure.
Proposed Design	We propose no additional bathrooms.

Reason for alternative It is currently unsafe to be near the shredder during operation. No occupants are allowed in the shredder enclosure during operation of the shredder. This is a 7,000 horsepower shredder that shreds existing cars, trucks, refrigerators, etc. From time to time pieces of shredded metal can exit the shredder during operation. Operation of the shredder can last for the entirety of a work shift.

> The shredder is an existing piece of equipment. No additional jobs or work are being created or modified by the addition of the shredder enclosure. The only reason for the addition of the enclosure is to capture air emissions from the shredder.

Also note that the shredder enclosure is not described in table 2902.1. 2902.1 states that uses not specifically listed shall be considered by the building official and shall reflect the use of the space being served by the fixtures. The use of this structure is as an emission capture enclosure over an existing piece of equipment.

Reconsideration Text

I have added attachment 19029F-G08.pdf showing the distances to bathrooms in the vicinity of the new enclosure. The proposed bathroom for the new 3DS building (Permit #21-081428-CO) is within 300' of the new enclosure.

APPEAL DECISION

Omission of plumbing fixtures in proposed equipment enclosure: Granted as proposed.

The Administrative Appeal Board finds that the information submitted by the appellant demonstrates that the approved modifications or alternate methods are consistent with the intent of the code; do not lessen health, safety, accessibility, life, fire safety or structural requirements; and that special conditions unique to this project make strict application of those code sections impractical.

Pursuant to City Code Chapter 24.10, you may appeal this decision to the Building Code Board of Appeal within 90 calendar days of the date this decision is published. For information on the appeals process, go to www.portlandoregon.gov/bds/appealsinfo, call (503) 823-7300 or come in to the Development Services Center.



PROJECT: SHREDDER ENCLOSURE AND AIR CONTROL

PORTLAND, OREGON

STRUCTURAL ENGINEER:

ELECTRICAL ENGINEER

OWNER:

SMG ENGINEERS INC.

8625 SW CASCADE AVENUE, SUITE 600 BEAVERTON, OR 97008 PHONE: (503) 643-8595

DAMATT ENGINEERING INC.

2420 CAMINO RAMON, SUITE 320 SAN RAMON, CA 94583 PHONE: (510) 891-0970

SCHNITZER STEEL INDUSTRIES, INC.

299 SW CLAY ST. SUITE 350 PORTLAND, OREGON, 97201 PHONE: (253) 993-9659

	DRAWING LIST	
DRAWING NUMBER	DESCRIPTION	
19-029F- G01	COVER SHEET, PROJECT LOCATION, DRAWING LIST	
19-029F- G02	GENERAL NOTES	
19-029F- G03	GENERAL NOTES	
19-029F- G04	PROJECT FLOW CHART	
19-029F- G05	EXIT PLAN	
19-029F- G06	DEMO PLAN - PLAN VIEW	
19-029F- G07	DEMO PLAN — ELEVATIONS	
19-029F- C01	SITE PLAN	
19-029F- C02	EXISTING FACILITIES	
19-029F- C03	MODIFICATION TO FACILITIES	
19-029F- C04	NEW GAS LINE METER LOCATION	
19-029F- C05	STORMWATER BASINS	
19-029F- C06	CONTOUR LINES	
19-029F- C07	CUT/FILL CONTOUR PLAN	
19-029F- C08	ERSC PLAN	
19-029F- C09	LAYDOWN YARDAGE	
19-029F- S01	GENERAL ARRANGEMENT — PLAN VIEW	
19-029F- S02	GENERAL ARRANGEMENT - WEST ELEVATIONS	
19-029F- S03	GENERAL ARRANGEMENT — EAST ELEVATIONS	
19-029F- S04	GENERAL ARRANGEMENT — NORTH & SOUTH ELEVATIONS	
19-029F- S05	FOUNDATION LAYOUT - PLAN VIEW	
19-029F- S06	FOUNDATION DETAILS — SHREDDER ENCLOSURE	
19-029F- S07	FOUNDATION DETAILS — DROPOUT BOX/VENTURI SCRUBBER & TANK	
19-029F- S08	FOUNDATION DETAILS — RTO STRUCTURE AND PDC BUILDING	
19-029F- S09	FOUNDATION DETAILS — AGS STRUCTURE AND COMPRESSOR BUILDING	
19-029F- S10	SHREDDER ENCLOSURE - PLAN VIEW	
19-029F- S11	SHREDDER ENCLOSURE — ELEVATIONS	
19-029F- S12	SHREDDER ENCLOSURE — ELEVATIONS	
19-029F- S13	SHREDDER ENCLOSURE — STRUCTURAL PLAN	
19-029F- S14	SHREDDER ENCLOSURE — STRUCTURAL ELEVATIONS	
19-029F- S15	SHREDDER ENCLOSURE — STRUCTURAL ELEVATIONS	
19-029F- S16	SHREDDER ENCLOSURE — STRUCTURAL ELEVATIONS	
19-029F- S17	REMOVABLE PANEL DETAILS	
19-029F- S18	REMOVABLE PANEL DETAILS	

19-029F- S19 REMOVABLE PANEL DETAILS

	DRAWING LIST	
DRAWING NUMBER	DESCRIPTION	
19-029F- S20	DUCT RUN — SHREDDER TO DROPOUT BOX	
19-029F- S21	DUCT SUPPORT DETAIL	
19-029F- S22	DROPOUT BOX STRUCTURE — PLAN AND ELEVATIONS	
19-029F- S23	DROPOUT BOX STRUCTURE — DETAILS	
19-029F- S24	DROPOUT BOX — DETAILS	
19-029F- S25	DROPOUT BOX — DETAILS	
19-029F- S26	DROPOUT BOX — DETAILS	
19-029F- S27	DROPOUT BOX — DETAILS	
19-029F- S28	DROPOUT BOX — DETAILS	
19-029F- S29	DUCT RUN - DROPOUT BOX TO VENTURI SCRUBBERS	
19-029F- S30	VENTURI SCRUBBER — PLAN AND ELEVATIONS	
19-029F- S31	VENTURI SCRUBBER – ELEVATIONS	
19-029F- S32	VENTURI SCRUBBER – ELEVATIONS	
19-029F- S33	VENTURI SCRUBBER – DETAILS	
19-029F- S34	VENTURI SCRUBBER – DETAILS	
19-029F- S35	DUCT RUN — VENTURI SCRUBBERS TO RTO	
19-029F- S40	RTO STRUCTURE — PLAN AND ELEVATIONS	
19-029F- S41	RTO STRUCTURE – ELEVATIONS	
19-029F- S42	THERMAL DUCT SUPPORT FRAME #1 - DETAILS	
19-029F- S43	THERMAL DUCT SUPPORT FRAME #2 — DETAILS	
19-029F- S44	AGS STRUCTURE - PLAN AND ELEVATIONS	
19-029F- S45	AGS STRUCTURE - PLAN AND ELEVATIONS	
19-029F- S46	AGS STRUCTURE - PLAN AND ELEVATIONS	
19-029F- S47	COMPRESSOR ROOM STRUCTURE — PLAN AND ELEVATIONS	
19-029F- S50	PUSH WALL	

DRAWING LIST (CONT.)		
DRAWING NUMBER	DESCRIPTION	
19-029F- S60	STANDARD GUARDRAIL DETAILS	
19-029F- S61	STANDARD LADDER DETAILS	
19-029F- S62	STANDARD STAIR DETAILS	
19-029F- S63	STANDARD GRATING DETAILS	
19-029F- S64	STANDARD BOLTED CONNECTION DETAILS	
19-029F- S65	STANDARD BOLTED CONNECTION DETAILS	
19-029F- S66	STANDARD BOLTED CONNECTION DETAILS	
19-029F- S69	STANDARD BASE PLATE DETAILS	
19-029F- S70	SHREDDER CONNECTION DETAILS	
19-029F- S71	SHREDDER CONNECTION DETAILS	
19-029F- S72	SHREDDER CONNECTION DETAILS	
19-029F- S80	DUCT DETAILS	
19-029F- S81	DUCT DETAILS	
19-029F- S82	DUCT DETAILS	
19-029F- S83	DUCT DETAILS	
19-029F- S84	DUCT DETAILS	
19-029F- S85	DUCT DETAILS	
19-029F- S90	CRANE ACCESS LAYOUT	
19-029F- S91	SHREDDER ENCLOSURE MAT LAYOUT	
19-029F- S92	SHREDDER ENCLOSURE MAT LAYOUT	
19-029F- S93	SHREDDER ENCLOSURE MAT LAYOUT	
19-029F- S94	SHREDDER ENCLOSURE MAT LAYOUT	



PROJECT INFORMATION:

- 12005 N BURGUARD RD
- PORTLAND, OR 97203
- SECTION 35 2N 1W, TL 500 67.77 ACRES UPLAND 7.43 ACRES LOWLAND, LAND & IMPS SEE R646262 (R971350713) FOR MACH & EQUIP

J.D. WALLACE

3. ZONE: HEAVY INDUSTRIAL

THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC. THE DESIGN SHOWN IN THIS DRAWING IS SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE BLOCK. IF THIS DRAWING IS NOT STAMPED WITH AN ENGINEER'S SEAL, THE DRAWING MAY HAVE BEEN REPRODUCED FROM AN UNAUTHORIZED COPY. AUTHORIZED CONTROL DOCUMENT IS EITHER A STAMPED HARD COPY OR DIGITALLY PROTECTED ORIGINAL. THIS DRAWING SHALL NOT BE USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS DRAWING IS AN AGREEMENT TO THE ABOVE. 02/11/22 0 ISSUED FOR PERMIT BY DATE CHK'D



	SIIS
Smith	Monroe Gray
ENG	INEERS, INC.

8625 SW Cascade Ave. Suite 600 Beaverton, Oregon 97008 Phone: 503.643.8595 Fax: 503.643.8610

www.smgengr.com

SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY NEW SHREDDER ENCLOSURE AND AIR CONTROL COVER SHEET, PROJECT LOCATION, DRAWING LIST

19-029F-G00 AS NOTED

REQUIRED VERIFICATION AND INSPECTION OF STEEL CONSTRUCTION

	VERIFICATION AND INSPECTION	CONTINUOUS	PERIODIC	REFERENCED STANDARD
•	MATERIAL VERIFICATION OF HIGH-STRENGTH BOLTS, NUTS AND WASHERS	<u> </u> 		
	A. IDENTIFICATION MARKINGS TO CONFORM TO ASTM STANDARDS SPECIFIED IN THE APPROVED CONSTRUCTION DOCUMENTS	_	Χ	AISC 360, SECTION A3 AND APPLICABLE ASTN MATERIAL STANDARDS
	B. MANUFACTURER'S CERTIFICATE OF COMPLIANCE REQUIRED	_	X	—
<u>.</u> .	INSPECTION OF HIGH-STRENGTH BOLTING:			
	A. SNUG-TIGHT JOINTS	_	Χ	
	B. PRETENSIONED AND SLIP-CRITICAL JOINTS USING TURN-OF-NUT WITH MATCHMARKING, TWIST-OFF BOLT OR DIRECT TENSION INDICATOR METHODS OF INSTALLATION	_	X	AISC 360, SECTION M2.5
	C. PRETENSIONED AND SLIP-CRITICAL JOINTS USING TURN-OF-NUT WITHOUT MATCHMARKING OR CALIBRATED WRENCH METHODS OF INSTALLATION	X	_	
3.	MATERIAL VERIFICATION OF STRUCTURAL STEEL AND COLD-FORMED STEE	EL DECK:		
	A. FOR STRUCTURAL STEEL, IDENTIFICATION MARKINGS TO CONFORM TO AISC 360	_	X	AISC 360, SECTION M5.5
	B. FOR OTHER STEEL, IDENTIFICATION MARKINGS TO CONFORM TO ASTM STANDARDS SPECIFIED IN THE APPROVED CONSTRUCTION DOCUMENTS	_	Χ	APPLICABLE ASTM MATERIAL STANDARDS
	C. MANUFACTURER'S CERTIFIED TEST REPORTS	_	Χ	
ŀ.	MATERIAL VERIFICATION OF WELD FILLER MATERIALS:			
	A. IDENTIFICATION MARKINGS TO CONFORM TO AWS SPECIFICATION IN THE APPROVED CONSTRUCTION DOCUMENTS	_	Χ	AISC 360, SECTION A3.5 AND APPLICABLE AWS A5 DOCUMENTS
	B. MANUFACTURER'S CERTIFICATE OF COMPLIANCE REQURIED	_	Х	_
5.	INSPECTION OF WELDING:			
	A. STRUCTURAL STEEL AND COLD-FORMED STEEL DECK:			
	1) COMPLETE AND PARTIAL JOINT PENETRATION GROOVE WELDS	X	_	
	2) MULTIPASS FILLET WELDS	X	_	
	3) SINGLE-PASS FILLET WELDS > 5/16"	X	_	AWS D1.1
	4) PLUG AND SLOT WELDS	X	_	
	5) SINGLE-PASS FILLET WELDS < OR = 5/16"	_	Χ	
	6) FLOOR AND ROOF DECK WELDS	_	Χ	AWS D1.3
	B. REINFORCING STEEL:			
	1) VERIFICATION OF WELDABILITY OF REINFORCING STEEL OTHER THAN ASTM A 706	_	Х	
	2) REINFORCING STEEL RESISTING FLEXURAL AND AXIAL FORCES IN INTERMEDIATE AND SPECIAL MOMENT FRAMES, AND BOUNDARY ELEMENTS OF SPECIAL STRUCTURAL WALLS OF CONCRETE AND SHEAR REINFOCEMENT	X	_	
	3) SHEAR REINFORCEMENT	X	_	AWS D1.4 ACI 318: SECTION 3.5.2
	4) OTHER REINFORCING STEEL	_	Χ	
6.	INSPECTION OF STEEL FRAME JOINT DETAILS FOR COMPLIANCE:			
	A. DETAILS SUCH AS BRACING AND STIFFENING	_	Χ	
	B. MEMBER LOCATIONS	_	Χ	_
_				1

C. APPLICATION OF JOINT DETAILS AT EACH CONNECTION

REQUIRED VERIFICATION AND INSPECTION OF CONCRETE CONSTRUCTION

	VERIFICATION AND INSPECTION	CONTINUOUS	PERIODIC	REFERENCED STANDARD
1.	INSPECTION OF REINFORCING STEEL, INCLUDING PRESTRESSING TENDONS, AND PLACEMENT	_	Χ	ACI 318: 3.5, 7.1-7.7
2.	INSPECTION OF REINFORCING STEEL WELDING IN ACCORDANCE WITH TABLE 1704.3, ITEM 5B	_	_	AWS D1.4 ACI 318: 3.5.2
3.	INSPECTION OF BOLTS TO BE INSTALLED IN CONCRETE PRIOR TO AND DURING PLACEMENT OF CONCRETE WHERE ALLOWABLE LOADS HAVE BEEN INCREASED OR WHERE STRENGTH DESIGN IS USED	Χ	_	ACI 318: 8.1.3, 21.2.8
4.	INSPECTION OF ANCHORS INSTALLED IN HARDENED CONCRETE	_	Χ	ACI 318: 3.8.6, 8.1.3, 21.2.8
5.	VERIFYING USE OF REQUIRED DESIGN MIX	_	Χ	ACI 318: CH. 4, 5.2-5.4
6.	AT THE TIME FRESH CONCRETE IS SAMPLED TO FABRICATE SPECIMENS FOR STRENGTH TESTS, PERFORM SLUMP AND AIR CONTENT TESTS, AND DETERMINE THE TEMPERATURE OF THE CONCRETE	X	_	ASTM C 172 ASTM C 31 ACI 318: 5.6, 5.8
7.	INSPECTION OF CONCRETE AND SHOTCRETE PLACEMENT FOR PROPER APPLICATION TECHNIQUES	X	_	ACI 318: 5.9, 5.10
8.	INSPECTION FOR MAINTENANCE OF SPECIFIED CURING TEMPERATURE AND TECHNIQUES	_	Χ	ACI 318: 5.11-5.13
9.	INSPECTION OF PRESTRESSED CONCRETE: A. APPLICATION OF PRESTRESSING FORCES B. GROUTING OF BONDED PRESTRESSING TENDONS IN THE SEISMIC—FORCE—RESISTING SYSTEM	X	_	ACI 318: 18.20 ACI 318: 18.18.4
10.	ERECTION OF PRECAST CONCRETE MEMBERS	_	Χ	ACI 318: CH. 16
11.	VERIFICATION OF IN-SITU CONCRETE STRENGTH, PRIOR TO STRESSING OF TENDONS IN POST-TENSIONED CONCRETE AND PRIOR TO REMOVAL OF SHORES AND FORMS FROM BEAMS AND STRUCTURAL SLABS	_	Χ	ACI 318: 6.2
12.	INSPECT FORMWORK FOR SHAPE, LOCATION AND DIMENSIONS OF THE CONCRETE MEMBER BEING FORMED	_	Χ	ACI 318: 6.1.1

REQUIRED VERIFICATION AND INSPECTION OF SOILS

	VERIFICATION AND INSPECTION TASK	CONTINUOUS	PERIODIC
1.	VERIFY MATERIALS BELOW SHALLOW FOUNDATIONS ARE ADEQUATE TO ACHIEVE THE DESIGN BEARING CAPACITY	_	Χ
2.	VERIFY EXCAVATIONS ARE EXTENDED TO PROPER DEPTH AND HAVE REACHED PROPER MATERIAL	_	X
3.	PERFORM CLASSIFICATION AND TESTING OF COMPACTED FILL MATERIALS	_	X
4.	VERIFY USE OF PROPER MATERIALS, DENSITIES AND LIFT THICKNESSES DURING PLACEMENT AND COMPACTION OF COMPACTED FILL	X	_
5.	PRIOR TO PLACEMENT OF COMPACTED FILL, OBSERVE SUBGRADE AND VERIFY THAT SITE HAS BEEN PREPARED PROPERLY	_	X

GENERAL NOTES AND SPECIFICATIONS

PROJECT SCOPE:

SCHNITZER STEEL INDUSTRIES INTENDS TO CONSTRUCT A NEW SHREDDER ENCLOSURE AND CORRESPONDING EMISSIONS CONTROL SYSTEM. THE EMISSION CONTROL SYSTEM INCLUDES PARTICLE TREATMENT AND VOC TREATMENT. THE MAIN SYSTEM INCLUDES THE ADDITION OF A DROP OUT BOX, (2) ABORT GATES (2) VENTURI SCRUBBERS, (2) FANS, (2) REGENERATIVE THERMAL OXIDIZERS AND (2) ACID-GAS SCRUBBERS. SMG SCOPE OF WORK INCLUDES STRUCTURAL SUPPORTS, ACCESS AND FOUNDATIONS FOR THE NEW EQUIPMENT.

GEOTECHNICAL:

- 1. REFER TO THE GEOTECHNICAL REPORT BY GRI.
- 2. FOR DEMOLITION, EXCAVATION AND SUBGRADE PREPARATION REQUIREMENTS SEE GEOTECHNICAL REPORT
- 3. THE DESIGN SAFE BEARING CAPACITY IS ASSUMED TO BE 2,000 PSF WITH SITE CLASS F.

REINFORCED CONCRETE:

- 1. ALL CAST-IN-PLACE CONCRETE SHALL DEVELOP A MINIMUM COMPRESSIVE STRESS OF 4000 PSI AT 28 DAYS. MAXIMUM SLUMP SHALL BE 4 INCHES — UNLESS NOTED OTHERWISE ON THE CONCRETE DRAWINGS.
- 2. CONCRETE SHALL USE TYPE II CEMENT AND MIX DESIGNED WITH A MAXIMUM WATER TO CEMENT RATIO OF 0.45.
- 3. READY-MIXED CONCRETE SHALL BE MIXED AND DELIVERED TO THE JOB SITE IN ACCORDANCE WITH THE REQUIREMENTS SET FORTH IN "SPECIFICATIONS FOR READY-MIXED CONCRETE" (ASTM C94).
- 4. ALL CONCRETE SHALL BE CONSOLIDATED BY SUITABLE MEANS DURING PLACEMENT AND SHALL BE THOROUGHLY WORKED AROUND REINFORCEMENT. EMBEDDED FIXTURES AND INTO CORNERS OF FORMS.
- 5. ALL FORMS TO BE CLEAN, WITH NO WATER OR LOOSE MATERIAL PRESENT.
- 6. DURING HOT WEATHER, PROPER ATTENTION SHALL BE GIVEN TO INGREDIENTS, PRODUCTION METHODS, HANDLING, PLACING, PROTECTION, AND CURING TO PREVENT EXCESSIVE CONCRETE TEMPERATURES OR WATER EVAPORATION THAT MAY IMPAIR REQUIRED STRENGTH OR SERVICEABILITY OF THE MEMBER OR STRUCTURE. REFER TO ACI 305.
- 7. NO CONCRETE ADMIXTURES SHALL BE USED WITHOUT PRIOR APPROVAL OF THE ENGINEER OR AS SPECIFIED IN THESE SPECIFICATIONS.
- 8. ALL EXPOSED CORNERS SHALL HAVE A 3/4" CHAMFER UNLESS NOTED OTHERWISE.
- 9. REINFORCING STEEL AND CONCRETE CONSTRUCTION SHALL CONFORM TO THE "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE" (ACI 318) AND ACI 315.
- 10. ALL PROPOSED COLD JOINTS TO BE REVIEWED BY THE ENGINEER. ALL COLD JOINTS TO BE ROUGHENED AND
- 11. REINFORCING STEEL SHALL CONFORM TO ASTM A615, GRADE 60, FOR DEFORMED BARS.
- 12. BARS IN SLABS SHALL BE SUPPORTED ON WELL-CURED CONCRETE BLOCKS, METAL OR PLASTIC CHAIRS, AS SPECIFIED BY THE CRSI MANUAL OF STANDARD PRACTICE, MSP-1. REINFORCING STEEL SHALL BE DETAILED IN ACCORDANCE WITH THE "ACI MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES." ACI 315. LAP ALL REINFORCING BARS PER THE TYPICAL LAP SPLICE LENGTH SCHEDULE, EXCEPT AS NOTED.
- 13. SPLICE LENGTHS SHALL BE AS SHOWN IN THE FOLLOWING TABLE, UNLESS NOTED OTHERWISE ON THE DRAWINGS:

BAR SIZE	SPLICE LENGTH	BAR SIZE	SPLICE LENGTH	
#4	25 IN.	#10	78 IN.	
#5	31 IN.	" 11	86 IN.	
#6	37 IN.	<i>"</i>		
 #7	54 IN.			
#8	61 IN.			
"				

- 14. BACKFILL MATERIAL SHALL BE AS RECOMMENDED IN BACKFILL NOTES.
- 15. ALL BLOCKOUTS, SLEEVES, OPENINGS, CONDUIT AND OTHER EMBEDDED ITEMS NOT SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE APPROVED BY THE STRUCTURAL ENGINEER BEFORE POURING. CONDUITS EMBEDDED IN SLABS SHALL NOT BE LARGER IN OUTSIDE DIMENSION THAN ONE THIRD OF THE THICKNESS OF THE SLAB AND SHALL NOT BE SPACED CLOSER THAN THREE DIAMETERS ON CENTER. VERIFY ALL BLOCKOUTS WITH MECHANICAL, ELECTRICAL AND PLUMBING REQUIREMENTS.
- 16. CONCRETE COVER REINFORCING STEEL AND OTHER EMBEDDED STEEL SHALL BE AS SHOWN ON DRAWING. IF NOT SHOWN, USE COVERS AS SPECIFIED IN ACI 318, AS NOTED BELOW:

CONCRETE CAST AGAINST EARTH3 INCHES	
CONCRETE EXPOSED TO EARTH OR WEATHER:	
#5 BAR AND SMALLER1 1/2 INCHES	
#6 BAR AND LARGER2 INCHES	
CONCRETE NOT EXPOSED TO EARTH NOR WEATHER:	
SLABS, WALLS, JOINTS3/4 INCH	
BEAMS, COLUMNS1 1/2 INCHES	

17. ELECTRICAL GROUNDING ELEMENTS SHALL BE IN PLACE PRIOR TO POURING CONCRETE.

GROUTING:

- 1. ALL BASE PLATES AND GROUT-POCKETS FOR SHEAR KEYS. SHALL BE GROUTED IN ACCORDANCE WITH AISC 303-05. 2. GROUT SHALL BE PRE-APPROVED BY THE ENGINEER AND SHALL BE HIGH STRENGTH, NON-SHRINK, NON-METALLIC.
- 3. GROUT SHALL BE INSTALLED AND ALL CONTACT SURFACES SHALL BE CLEANED AND PREPARED BEFOREHAND IN ACCORDANCE WITH THE GROUT-SUPPLIER'S SPECIFICATIONS.

STRUCTURAL STEEL:

STRUCTURAL STEEL SHALL CONFORM TO:

ASTM A992	WIDE FLANGE AND TEES
ASTM A36	CHANNELS, PLATES AND ANGLES, EXCEPT AS NOTED.
ASTM A500, GRADE B	HOLLOW STRUCTURAL SECTIONS (TUBES)
ASTM A53, GRADE B	PIPES
ASTM A572 GR 50	PLATES WHERE NOTED IN DRAWINGS

- 1. DESIGN, FABRICATION, AND ERECTION SHALL BE IN ACCORDANCE WITH AISC 360-05 "SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS" WITH "COMMENTARY" AND THE "CODE OF STANDARD PRACTICE", WITH EXCEPTIONS NOTED IN SPECIFICATIONS.
- 2. BOLTS IN PRIMARY STRUCTURAL CONNECTIONS SHALL CONFORM TO ASTM A325.

CEMENTITIOUS OR EPOXY-TYPE - UNLESS NOTED OTHERWISE ON THE DRAWINGS.

- 3. STANDARD STRUCTURAL WASHERS SHALL CONFORM TO ASTM F436.
- 4. ANCHOR RODS SHALL CONFORM TO ASTM F1554 GR 36 UNO ON THE CONCRETE DRAWINGS.
- 5. POST INSTALLED ANCHORS SHALL BE AS SHOWN ON THE DESIGN DRAWINGS BACKED BY REQUIRED ICC TEST REPORTS.
- 6. WELDING SHALL CONFORM TO AWS D1.1 CODE FOR ARC AND GAS WELDING IN BUILDING CONSTRUCTION. WELDING SHALL BE PERFORMED IN ACCORDANCE WITH A WELDING PROCEDURE SPECIFICATION (WPS) AS REQUIRED IN AWS D1.1 AND APPROVED BY THE ENGINEER. THE WPS VARIABLES SHALL BE WITHIN THE PARAMETERS ESTABLISHED BY THE FILLER-METAL MANUFACTURER.
- 7. ALL CONNECTIONS, UNLESS NOTED OTHERWISE, SHALL BE FULLY WELDED CONNECTIONS. FILLET WELD SIZE TO BE 1/16" LESS THAN THE THINNEST MATERIAL WITH A MINIMUM OF 3/16". BUTT WELDS TO BE COMPLETE JOINT PENETRATION (CJP) BUTT OR BEVEL WELDS IN ACCORDANCE WITH AWS.
- 8. WELDS SHALL BE MADE USING E70 ELECTRODES. ALL STRUCTURAL WELDING SHALL BE BY AWS CERTIFIED WELDERS.

CONTRACTOR REQUIREMENTS:

- 1. THE CONTRACTOR SHALL COORDINATE SEISMIC RESTRAINTS OF MECHANICAL, PLUMBING AND ELECTRICAL EQUIPMENT, MACHINERY, AND ASSOCIATED PIPING WITH THE STRUCTURE.
- 2. FIELD ENGINEERED DETAILS DEVELOPED BY THE CONTRACTOR THAT DIFFER FROM OR ADD TO THE STRUCTURAL DRAWINGS SHALL BEAR THE SEAL AND SIGNATURE OF A STRUCTURAL ENGINEER REGISTERED IN CALIFORNIA AND SHALL BE SUBMITTED TO THE EOR PRIOR TO CONSTRUCTION.
- 3. THE GENERAL INSTALLATION CONTRACTOR SHALL VERIFY ALL DIMENSIONS AT THE SITE. ALL DISCREPANCIES SHALL BE CALLED TO THE ATTENTION OF THE ENGINEER AND BE RESOLVED PRIOR TO PROCEEDING WITH THE WORK.
- 4. THE CONTRACTOR IS TO PROVIDE BARRICADES, SIGNS, LIGHTS OR OTHER DEVICES AROUND THE WORK SITE AS REQUIRED AND/OR AS DIRECTED BY SAFETY PERSONAL.
- 5. LOCATION OF EXISTING UNDERGROUND UTILITIES ARE NOT CLEARLY KNOWN; CONTRACTOR TO TAKE CARE WITH EXCAVATIONS AND CONSTRUCTION.
- 6. ALL MATERIAL AND WORKMANSHIP TO CONFORM TO APPROPRIATE CODES AND STANDARDS.
- 7. THE CURRENT EDITION OF ALL REFERENCED CODES, STANDARDS AND SPECIFICATIONS SHALL GOVERN.
- 8. THE CONTRACTOR SHALL COMPLY WITH CALIFORNIA-OSHA GUIDELINES, BE RESPONSIBLE FOR ALL CONSTRUCTION METHODS, TEMPORARY SHORING, BRACING, TECHNIQUES, SEQUENCING AND SAFETY REQUIRED FOR CONSTRUCTION.
- 9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR STABILITY OF THE STRUCTURE DURING CONSTRUCTION. THE
- STRUCTURE SHOWN IN GENERAL ARRANGEMENT DRAWINGS IS STABLE IN THE COMPLETED CONFIGURATION ONLY.

PAINT COATINGS:

1ALL NEW STRUCTURAL STEEL SHALL BE PREPARED AND COATED IN ACCORDANCE WITH THE SSPC AND OWNER'S FINAL APPROVAL OF COLORS AS SPECIFIED. THIRD PARTY PAINT THICKNESS TESTING, MAY BE REQUIRED TO BE DONE PER DISCRETION OF OWNER'S PROJECT REPRESENTATIVE.

GENERAL: ALL NEW STRUCTURAL STEEL SHALL RECEIVE SSPC-SP6 COMMERCIAL SANDBLAST ON ALL EXPOSED SURFACES. MINIMUM ACCEPTABLE SURFACE PREPARATION TO BE: POWER TOOL CLEANING (SSPC-SP3) WHICH INCLUDES SOLVENT CLEANING (SSPC-SP1).

ALL EXPOSED STEEL SURFACES:

DO NOT PAINT AREAS TO BE FIELD WELDED.

PRIMER: APPLY (1) COAT OF "WASSER MC-ZINC 100" - 4.0MILS [MIN] DRY FILM THICKNESS. TOP COAT: APPLY (1) COAT OF "WASSER MC-FERROX A" - 4.0MILS [MIN] DRY FILM THICKNESS

- ALL GUARDRAILS, LADDERS, STAIR NOZING AND LIFT LUGS: COLOR TO BE OSHA SAFETY YELLOW

AS NOTED

- ALL STRUCTURAL AND FABRICATED PLATE COMPONENTS: COLOR TO BE GRAY TO MATCH EXISTING STEELWORK AND PER OWNER'S PRE-APPROVAL].

WELD-DISTURBED AREAS: AFTER FIELD WELDING AND FOR FIELD TOUCH-UP OF PAINTED SURFACES: PREP AFFECTED AREAS WITH SSPC-SP2-3, HAND CLEAN OR POWER TOOL, AND APPLY THE APPLICABLE COATING SYSTEM

SUBMITTALS:

AS OUTLINED ABOVE.

SHOP DRAWINGS SHALL BE SUBMITTED TO THE ENGINEER OF RECORD (EOR) AND REVIEWED PRIOR TO FABRICATION AND CONSTRUCTION REGARDING ALL STRUCTURAL ITEMS


1. ANY CHANGES TO THE STRUCTURAL DRAWINGS SHALL BE SUBMITTED TO THE EOR AND ARE SUBJECT TO REVIEW AND ACCEPTANCE BY THE EOR.

THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC THE DESIGN SHOWN IN THIS DRAWING IS SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE BLOCK. IF THIS DRAWING IS NOT STAMPED WITH AN ENGINEER'S SEAL, THE DRAWING MAY HAVE BEEN REPRODUCED FROM AN UNAUTHORIZED COPY. AUTHORIZED CONTROL DOCUMENT IS EITHER A STAMPED HARD COPY OR DIGITALLY PROTECTED ORIGINAL. THIS DRAWING SHALL NOT BE USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS DRAWING IS AN AGREEMENT TO THE ABOVE. 0 ISSUED FOR PERMIT

REVISIONS

BY

DATE CHK'D





6/18/21

J.D. WALLACE

8625 SW Cascade Ave. Suite 600 Phone: 503.643.8595 Fax: 503.643.8610

SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY NEW SHREDDER ENCLOSURE AND AIR CONTROL

19-029F-G02

Beaverton, Oregon 97008 Smith Monroe Gray GENERAL NOTES www.smgengr.com

GENERAL DESIGN CRITERIA

STRUCTURAL DESIGN WAS BASED ON THE STRENGTH AND DEFLECTION CRITERIA OF THE 2018 IBC AND 2019 OSSC MODIFICATIONS. IN ADDITION TO THE SELF-WEIGHT OF THE STRUCTURAL ELEMENTS, THE FOLLOWING LOADS AND CRITERIA WERE USED:

DESIGN LOADS:

RISK CATEGORY II

<u>DEAD LOAD</u>

ACTUAL WEIGHT OF MATERIALS OF CONSTRUCTION AND PERMANENT EQUIPMENT

LIVE LOAD

ROOF DECK 25 PSF UNIFORM

ACCESS PLATFORM [D.O.B.]

60 PSF UNIFORM 1,000 LB CONCENTRATED

ELEVATED WALKWAY

40 PSF UNIFORM 1,000 LB CONCENTRATED

STAIRS AND LANDINGS

100 PSF UNIFORM 1,000 LB CONCENTRATED

FALL ARREST TIE-OFF POST:

2,250LB

SNOW LOAD
SNOW IMPORTANCE FACTOR, ls = 1.0

10 PSF GROUND SNOW LOAD ROOF SNOW LOAD

25 PSF (INCLUDED 5 PSF RAIN SURCHARGE)

WIND LOAD

BASIC WIND SPEED (3-SECOND GUST), V=96 MPH WIND IMPORTANCE FACTOR, lw = 1.0

EXPOSURE

SEISMIC LOAD SEISMIC IMPORTANCE FACTOR, le = 1.0

[PER GEOTECHNICAL INVESTIGATION REPORT BY GRI, ISSUED 3/23/2021.]

SITE CLASS

MAPPED SPECTRAL RESPONSE ACCELERATION

SHORT PERIOD, Ss 1 SECOND PERIOD, S1 0.41g

SPECTRAL RESPONSE COEFFICIENTS

SHORT PERIOD, Sds 0.54 1 SECOND PERIOD, Sd1 1.09

SEISMIC DESIGN CATEGORY

SOIL LOAD BEARING PER GEOTECHNICAL INVESTIGATION REPORT BY GRI, ISSUED 3/23/2021.

ALLOWABLE BEARING PRESSURE

2,000 PSF LONG TERM LOADS 2,666 PSF SHORT TERM LOADS

32.4 FT

FLOOD LOAD (FOR EQUIPMENT AND STRUCTURES BELOW EL. 34.5 FT, NAVD88)

<u>COP</u> 28.9 FT BASE 100 YEAR FLOOD ELEVATION 1996 FLOOD INUNDATION ELEVATION 32.5 FT 30.4 FT

FLOOD PROTECTION ELEVATION (2 FT FREEBOARD) 34.5 FT BUOYANCY FORCE (DISPLACED VOLUME) 62.4 PCF

62.4 PCF HYDROSTATIC PRESSURE

LOAD COMBINATIONS:

APPLICABLE FACTORS AS LISTED IN ASCE 7-16

EQUIPMENT ENCLOSURES & SUPPORTS: SPECIFIC SEISMIC DESIGN CRITERIA

THE FOLLOWING LATERAL FORCE RESISTING SYSTEMS, RESPONSE MODIFICATION COEFFICIENTS AND LATERAL DESIGN FACTORS ARE APPLICABLE TO THE DESIGN OF EQUIPMENT ENCLOSURES & SUPPORT STRUCTURES, IN ACCORDANCE WITH 2019 OSSC (REF. ASCE7-16 AND SEISMIC DESIGN MANUAL).

SHREDDER ENCLOSURE:

OCBF 2.5

DUCT & WALKWAY SUPPORT BENTS:

OCBF [TRUSSED TOWER]

DROP OUT BOX [DOB] SUPPORT STRUCTURE:

LRFS OCBF [TRUSSED TOWER]

0.24

<u>VENTURI-SCRUBBERS' AND OUTLET DUCT SUPPORT STRUCTURES:</u>

OCBF 2.5 0.24

REGENERATIVE THERMAL OXIDIZER [RTO] SUPPORT STRUCTURE:

OCBF 2.5 0.24

ACID GAS SCRUBBERS' [AGS] SUPPORT STRUCTURE:

2.5 0.24

COMPRESSOR ROOM:

OCBF[E/W] OMF [N/S] LRFS 3.25 0.19

THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC. THE DESIGN SHOWN IN THIS DRAWING IS

SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE

BLOCK. IF THIS DRAWING IS NOT STAMPED

WITH AN ENGINEER'S SEAL, THE DRAWING MAY HAVE BEEN REPRODUCED FROM AN UNAUTHORIZED COPY. AUTHORIZED

CONTROL DOCUMENT IS EITHER A STAMPED

DRAWING IS AN AGREEMENT TO THE ABOVE.


0 ISSUED FOR PERMIT

REVISIONS

HARD COPY OR DIGITALLY PROTECTED ORIGINAL. THIS DRAWING SHALL NOT BE USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS

POWER DISTRIBUTION CENTER [PDC] SUPPORT FOOTING:

2.5 Cs[EFFECTIVE] 0.31



| JL | 01/17/22 | JWC

BY DATE CHK'D



J.D. WALLACE

8625 SW Cascade Ave. Suite 600

Beaverton, Oregon 97008 Phone: 503.643.8595 Fax: 503.643.8610


www.smgengr.com


SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY


NEW SHREDDER ENCLOSURE AND AIR CONTROL


GENERAL NOTES


19-029F-G03 AS NOTED 6/18/21


























A NORTH ELEVATION @ AGS & VENTURI SCRUBBER S04 1/8" = 1'-0"



B SOUTH ELEVATION @ RTO, COMPRESSOR ROOM & PDC SO4 1/8" = 1'-0"





Smith Monroe Gray
ENGINEERS, INC.

Phone: 503,643,8595
Fax: 503,643,8610

DRAWN BY
J. LUM

PATE

CHKD BY

B8625 SW Cascade Ave.
Suite 600
Beaverton, Oregon 97008
Beaverton, Oregon 97008

Phone: 503,643,8595
Fax: 503,643,8610


NEW SHREDDER ENCLOSURE AND AIR CONTROL


NEW FOUNDATION LAYOUT


REV.
AS NOTED


REV.
AS NOTED

19-029F-S05











THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC. THE DESIGN SHOWN IN THIS DRAWING IS SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE BLOCK. IF THIS DRAWING IS NOT STAMPED 8625 SW Cascade Ave. Suite 600 Beaverton, Oregon 97008 SCHNITZER STEEL INDUSTRIES, INC.

PORTLAND FACILITY

NEW SHREDDER ENCLOSURE AND AIR CONTROL Smith Monroe Gray WITH AN ENGINEER'S SEAL, THE DRAWING
MAY HAVE BEEN REPRODUCED FROM AN
UNAUTHORIZED COPY. AUTHORIZED
CONTROL DOCUMENT IS EITHER A STAMPED
HARD COPY OR DIGITALLY PROTECTED Phone: 503.643.8595 Fax: 503.643.8610 ENGINEERS, INC. ELEVATIONS - NEW SCHREDDER ENCLOSURE www.smgengr.com ORIGINAL. THIS DRAWING SHALL NOT BE DRAWN BY USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS DRAWING IS AN AGREEMENT TO THE ABOVE. J.D. WALLACE 7/27/21 19-029F-S12 0
 JL
 01/17/22
 JWC

 BY
 DATE
 CHK'D
 AS NOTED O ISSUED FOR PERMIT EXPIRES: 12-31-23 REVISIONS







	THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC.						
	THE DESIGN SHOWN IN THIS DRAWING IS						
	SITE SPECIFIC AND SHALL BE USED ONLY						
	OR THE PROJECT SHOWN ON THE TITLE						
	BLOCK. IF THIS DRAWING IS NOT STAMPED						
	WITH AN ENGINEER'S SEAL, THE DRAWING MAY HAVE BEEN REPRODUCED FROM AN						
	JNAUTHORIZED COPY, AUTHORIZED						
	CONTROL DOCUMENT IS EITHER A STAMPED						
	HARD COPY OR DIGITALLY PROTECTED						
	ORIGINAL. THIS DRAWING SHALL NOT BE						
	JSED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS						
-	DRAWING IS AN AGREEMENT TO THE ABOVE.	0	ISSUED FOR PERMIT	JWC	07/29/22		
		SYM.	REVISIONS	BY	DATE	CHK'D	

					1:1	
Smith Monroe Gray ENGINEERS, INC.			25 SW Cascade Ave. Suite 600 verton, Oregon 97008 one: 503.643.8595 ax: 503.643.8610 vww.smgengr.com	SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY NEW SHREDDER ENCLOSURE AND AIR CONTROL BATHROOM DISTANCES		
DRAWN BY	DATE	CHKD BY	DATE	SCALE	DWG. NO.	REV.
JWC	07/29/22			AS NOTED	19-029F-G08	0



PROJECT: SHREDDER ENCLOSURE AND AIR CONTROL

PORTLAND, OREGON

STRUCTURAL ENGINEER:

ELECTRICAL ENGINEER

OWNER:

SMG ENGINEERS INC.

8625 SW CASCADE AVENUE, SUITE 600 BEAVERTON, OR 97008 PHONE: (503) 643-8595

DAMATT ENGINEERING INC.

2420 CAMINO RAMON, SUITE 320 SAN RAMON, CA 94583 PHONE: (510) 891-0970

SCHNITZER STEEL INDUSTRIES, INC.

299 SW CLAY ST. SUITE 350 PORTLAND, OREGON, 97201 PHONE: (253) 993-9659

	DRAWING LIST		
DRAWING NUMBER	DESCRIPTION		
19-029F- G01	COVER SHEET, PROJECT LOCATION, DRAWING LIST		
19-029F- G02	GENERAL NOTES		
19-029F- G03	GENERAL NOTES		
19-029F- G04	PROJECT FLOW CHART		
19-029F- G05	EXIT PLAN		
19-029F- G06	DEMO PLAN - PLAN VIEW		
19-029F- G07	DEMO PLAN — ELEVATIONS		
19-029F- C01	SITE PLAN		
19-029F- C02	EXISTING FACILITIES		
19-029F- C03	MODIFICATION TO FACILITIES		
19-029F- C04	NEW GAS LINE METER LOCATION		
19-029F- C05	STORMWATER BASINS		
19-029F- C06	CONTOUR LINES		
19-029F- C07	CUT/FILL CONTOUR PLAN		
19-029F- C08	ERSC PLAN		
19-029F- C09	LAYDOWN YARDAGE		
19-029F- S01	GENERAL ARRANGEMENT — PLAN VIEW		
19-029F- S02	GENERAL ARRANGEMENT - WEST ELEVATIONS		
19-029F- S03	GENERAL ARRANGEMENT — EAST ELEVATIONS		
19-029F- S04	GENERAL ARRANGEMENT — NORTH & SOUTH ELEVATIONS		
19-029F- S05	FOUNDATION LAYOUT - PLAN VIEW		
19-029F- S06	FOUNDATION DETAILS — SHREDDER ENCLOSURE		
19-029F- S07	FOUNDATION DETAILS — DROPOUT BOX/VENTURI SCRUBBER & TANK		
19-029F- S08	FOUNDATION DETAILS — RTO STRUCTURE AND PDC BUILDING		
19-029F- S09	FOUNDATION DETAILS — AGS STRUCTURE AND COMPRESSOR BUILDING		
19-029F- S10	SHREDDER ENCLOSURE - PLAN VIEW		
19-029F- S11	SHREDDER ENCLOSURE — ELEVATIONS		
19-029F- S12	SHREDDER ENCLOSURE — ELEVATIONS		
19-029F- S13	SHREDDER ENCLOSURE — STRUCTURAL PLAN		
19-029F- S14	SHREDDER ENCLOSURE — STRUCTURAL ELEVATIONS		
19-029F- S15	SHREDDER ENCLOSURE — STRUCTURAL ELEVATIONS		
19-029F- S16	SHREDDER ENCLOSURE — STRUCTURAL ELEVATIONS		
19-029F- S17	REMOVABLE PANEL DETAILS		
19-029F- S18	REMOVABLE PANEL DETAILS		

19-029F- S19 REMOVABLE PANEL DETAILS

DRAWING LIST		
DRAWING NUMBER	DESCRIPTION	
19-029F- S20	DUCT RUN — SHREDDER TO DROPOUT BOX	
19-029F- S21	DUCT SUPPORT DETAIL	
19-029F- S22	DROPOUT BOX STRUCTURE — PLAN AND ELEVATIONS	
19-029F- S23	DROPOUT BOX STRUCTURE — DETAILS	
19-029F- S24	DROPOUT BOX — DETAILS	
19-029F- S25	DROPOUT BOX — DETAILS	
19-029F- S26	DROPOUT BOX — DETAILS	
19-029F- S27	DROPOUT BOX — DETAILS	
19-029F- S28	DROPOUT BOX — DETAILS	
19-029F- S29	DUCT RUN - DROPOUT BOX TO VENTURI SCRUBBERS	
19-029F- S30	VENTURI SCRUBBER — PLAN AND ELEVATIONS	
19-029F- S31	VENTURI SCRUBBER – ELEVATIONS	
19-029F- S32	VENTURI SCRUBBER – ELEVATIONS	
19-029F- S33	VENTURI SCRUBBER – DETAILS	
19-029F- S34	VENTURI SCRUBBER – DETAILS	
19-029F- S35	DUCT RUN — VENTURI SCRUBBERS TO RTO	
19-029F- S40	RTO STRUCTURE — PLAN AND ELEVATIONS	
19-029F- S41	RTO STRUCTURE — ELEVATIONS	
19-029F- S42	THERMAL DUCT SUPPORT FRAME #1 - DETAILS	
19-029F- S43	THERMAL DUCT SUPPORT FRAME #2 — DETAILS	
19-029F- S44	AGS STRUCTURE - PLAN AND ELEVATIONS	
19-029F- S45	AGS STRUCTURE - PLAN AND ELEVATIONS	
19-029F- S46	AGS STRUCTURE – PLAN AND ELEVATIONS	
19-029F- S47	COMPRESSOR ROOM STRUCTURE - PLAN AND ELEVATIONS	
19-029F- S50	PUSH WALL	

DRAWING LIST (CONT.)			
DRAWING NUMBER	DESCRIPTION		
19-029F- S60 STANDARD GUARDRAIL DETAILS			
19-029F- S61	STANDARD LADDER DETAILS		
19-029F- S62	STANDARD STAIR DETAILS		
19-029F- S63	STANDARD GRATING DETAILS		
19-029F- S64	STANDARD BOLTED CONNECTION DETAILS		
19-029F- S65	STANDARD BOLTED CONNECTION DETAILS		
19-029F- S66	STANDARD BOLTED CONNECTION DETAILS		
19-029F- S69	STANDARD BASE PLATE DETAILS		
19-029F- S70	SHREDDER CONNECTION DETAILS		
19-029F- S71	S71 SHREDDER CONNECTION DETAILS		
19-029F- S72	SHREDDER CONNECTION DETAILS		
19-029F- S80	DUCT DETAILS		
19-029F- S81	DUCT DETAILS		
19-029F- S82	DUCT DETAILS		
19-029F- S83	DUCT DETAILS		
19-029F- S84	DUCT DETAILS		
19-029F- S85	DUCT DETAILS		
19-029F- S90	CRANE ACCESS LAYOUT		
19-029F- S91	SHREDDER ENCLOSURE MAT LAYOUT		
19-029F- S92	SHREDDER ENCLOSURE MAT LAYOUT		
19-029F- S93	SHREDDER ENCLOSURE MAT LAYOUT		
19-029F- S94	SHREDDER ENCLOSURE MAT LAYOUT		



PROJECT INFORMATION:

- 12005 N BURGUARD RD
- PORTLAND, OR 97203
- SECTION 35 2N 1W, TL 500 67.77 ACRES UPLAND 7.43 ACRES LOWLAND, LAND & IMPS SEE R646262 (R971350713) FOR MACH & EQUIP

J.D. WALLACE

3. ZONE: HEAVY INDUSTRIAL

THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC. THE DESIGN SHOWN IN THIS DRAWING IS SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE BLOCK. IF THIS DRAWING IS NOT STAMPED WITH AN ENGINEER'S SEAL, THE DRAWING MAY HAVE BEEN REPRODUCED FROM AN UNAUTHORIZED COPY. AUTHORIZED CONTROL DOCUMENT IS EITHER A STAMPED HARD COPY OR DIGITALLY PROTECTED ORIGINAL. THIS DRAWING SHALL NOT BE USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS DRAWING IS AN AGREEMENT TO THE ABOVE. 02/11/22 0 ISSUED FOR PERMIT BY DATE CHK'D



	SIIS
Smith	Monroe Gray
ENG	INEERS, INC.

8625 SW Cascade Ave. Suite 600 Beaverton, Oregon 97008 Phone: 503.643.8595 Fax: 503.643.8610

www.smgengr.com

SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY NEW SHREDDER ENCLOSURE AND AIR CONTROL COVER SHEET, PROJECT LOCATION, DRAWING LIST

19-029F-G00 AS NOTED

REQUIRED VERIFICATION AND INSPECTION OF STEEL CONSTRUCTION

	VERIFICATION AND INSPECTION	CONTINUOUS	PERIODIC	REFERENCED STANDARD
•	MATERIAL VERIFICATION OF HIGH-STRENGTH BOLTS, NUTS AND WASHERS	<u> </u> 		
	A. IDENTIFICATION MARKINGS TO CONFORM TO ASTM STANDARDS SPECIFIED IN THE APPROVED CONSTRUCTION DOCUMENTS	_	Χ	AISC 360, SECTION A3 AND APPLICABLE ASTN MATERIAL STANDARDS
	B. MANUFACTURER'S CERTIFICATE OF COMPLIANCE REQUIRED	_	X	—
<u>.</u> .	INSPECTION OF HIGH-STRENGTH BOLTING:			
	A. SNUG-TIGHT JOINTS	_	Χ	
	B. PRETENSIONED AND SLIP-CRITICAL JOINTS USING TURN-OF-NUT WITH MATCHMARKING, TWIST-OFF BOLT OR DIRECT TENSION INDICATOR METHODS OF INSTALLATION	_	X	AISC 360, SECTION M2.5
	C. PRETENSIONED AND SLIP-CRITICAL JOINTS USING TURN-OF-NUT WITHOUT MATCHMARKING OR CALIBRATED WRENCH METHODS OF INSTALLATION	X	_	
3.	MATERIAL VERIFICATION OF STRUCTURAL STEEL AND COLD-FORMED STEE	EL DECK:		
	A. FOR STRUCTURAL STEEL, IDENTIFICATION MARKINGS TO CONFORM TO AISC 360	_	X	AISC 360, SECTION M5.5
	B. FOR OTHER STEEL, IDENTIFICATION MARKINGS TO CONFORM TO ASTM STANDARDS SPECIFIED IN THE APPROVED CONSTRUCTION DOCUMENTS	_	Χ	APPLICABLE ASTM MATERIAL STANDARDS
	C. MANUFACTURER'S CERTIFIED TEST REPORTS	_	Χ	
ŀ.	MATERIAL VERIFICATION OF WELD FILLER MATERIALS:			
	A. IDENTIFICATION MARKINGS TO CONFORM TO AWS SPECIFICATION IN THE APPROVED CONSTRUCTION DOCUMENTS	_	Χ	AISC 360, SECTION A3.5 AND APPLICABLE AWS A5 DOCUMENTS
	B. MANUFACTURER'S CERTIFICATE OF COMPLIANCE REQURIED	_	Х	_
5.	INSPECTION OF WELDING:			
	A. STRUCTURAL STEEL AND COLD-FORMED STEEL DECK:			
	1) COMPLETE AND PARTIAL JOINT PENETRATION GROOVE WELDS	X	_	
	2) MULTIPASS FILLET WELDS	X	_	
	3) SINGLE-PASS FILLET WELDS > 5/16"	X	_	AWS D1.1
	4) PLUG AND SLOT WELDS	X	_	
	5) SINGLE-PASS FILLET WELDS < OR = 5/16"	_	Χ	
	6) FLOOR AND ROOF DECK WELDS	_	Χ	AWS D1.3
	B. REINFORCING STEEL:			
	1) VERIFICATION OF WELDABILITY OF REINFORCING STEEL OTHER THAN ASTM A 706	_	Х	
	2) REINFORCING STEEL RESISTING FLEXURAL AND AXIAL FORCES IN INTERMEDIATE AND SPECIAL MOMENT FRAMES, AND BOUNDARY ELEMENTS OF SPECIAL STRUCTURAL WALLS OF CONCRETE AND SHEAR REINFOCEMENT	X	_	
	3) SHEAR REINFORCEMENT	Х	_	AWS D1.4 ACI 318: SECTION 3.5.2
	4) OTHER REINFORCING STEEL	_	Χ	
6.	INSPECTION OF STEEL FRAME JOINT DETAILS FOR COMPLIANCE:			
	A. DETAILS SUCH AS BRACING AND STIFFENING	_	Χ	
	B. MEMBER LOCATIONS	_	Χ	_
_				1

C. APPLICATION OF JOINT DETAILS AT EACH CONNECTION

REQUIRED VERIFICATION AND INSPECTION OF CONCRETE CONSTRUCTION

	VERIFICATION AND INSPECTION	CONTINUOUS	PERIODIC	REFERENCED STANDARD
1.	INSPECTION OF REINFORCING STEEL, INCLUDING PRESTRESSING TENDONS, AND PLACEMENT	_	Χ	ACI 318: 3.5, 7.1-7.7
2.	INSPECTION OF REINFORCING STEEL WELDING IN ACCORDANCE WITH TABLE 1704.3, ITEM 5B	_	_	AWS D1.4 ACI 318: 3.5.2
3.	INSPECTION OF BOLTS TO BE INSTALLED IN CONCRETE PRIOR TO AND DURING PLACEMENT OF CONCRETE WHERE ALLOWABLE LOADS HAVE BEEN INCREASED OR WHERE STRENGTH DESIGN IS USED	Χ	_	ACI 318: 8.1.3, 21.2.8
4.	INSPECTION OF ANCHORS INSTALLED IN HARDENED CONCRETE	_	Χ	ACI 318: 3.8.6, 8.1.3, 21.2.8
5.	VERIFYING USE OF REQUIRED DESIGN MIX	_	Χ	ACI 318: CH. 4, 5.2-5.4
6.	AT THE TIME FRESH CONCRETE IS SAMPLED TO FABRICATE SPECIMENS FOR STRENGTH TESTS, PERFORM SLUMP AND AIR CONTENT TESTS, AND DETERMINE THE TEMPERATURE OF THE CONCRETE	X	_	ASTM C 172 ASTM C 31 ACI 318: 5.6, 5.8
7.	INSPECTION OF CONCRETE AND SHOTCRETE PLACEMENT FOR PROPER APPLICATION TECHNIQUES	X	_	ACI 318: 5.9, 5.10
8.	INSPECTION FOR MAINTENANCE OF SPECIFIED CURING TEMPERATURE AND TECHNIQUES	_	Χ	ACI 318: 5.11-5.13
9.	INSPECTION OF PRESTRESSED CONCRETE: A. APPLICATION OF PRESTRESSING FORCES B. GROUTING OF BONDED PRESTRESSING TENDONS IN THE SEISMIC—FORCE—RESISTING SYSTEM	X	_	ACI 318: 18.20 ACI 318: 18.18.4
10.	ERECTION OF PRECAST CONCRETE MEMBERS	_	Χ	ACI 318: CH. 16
11.	VERIFICATION OF IN-SITU CONCRETE STRENGTH, PRIOR TO STRESSING OF TENDONS IN POST-TENSIONED CONCRETE AND PRIOR TO REMOVAL OF SHORES AND FORMS FROM BEAMS AND STRUCTURAL SLABS	_	Χ	ACI 318: 6.2
12.	INSPECT FORMWORK FOR SHAPE, LOCATION AND DIMENSIONS OF THE CONCRETE MEMBER BEING FORMED	_	Χ	ACI 318: 6.1.1

REQUIRED VERIFICATION AND INSPECTION OF SOILS

	VERIFICATION AND INSPECTION TASK	CONTINUOUS	PERIODIC
1.	VERIFY MATERIALS BELOW SHALLOW FOUNDATIONS ARE ADEQUATE TO ACHIEVE THE DESIGN BEARING CAPACITY	_	Χ
2.	VERIFY EXCAVATIONS ARE EXTENDED TO PROPER DEPTH AND HAVE REACHED PROPER MATERIAL	_	X
3.	PERFORM CLASSIFICATION AND TESTING OF COMPACTED FILL MATERIALS	_	X
4.	VERIFY USE OF PROPER MATERIALS, DENSITIES AND LIFT THICKNESSES DURING PLACEMENT AND COMPACTION OF COMPACTED FILL	X	_
5.	PRIOR TO PLACEMENT OF COMPACTED FILL, OBSERVE SUBGRADE AND VERIFY THAT SITE HAS BEEN PREPARED PROPERLY	_	X

GENERAL NOTES AND SPECIFICATIONS

PROJECT SCOPE:

SCHNITZER STEEL INDUSTRIES INTENDS TO CONSTRUCT A NEW SHREDDER ENCLOSURE AND CORRESPONDING EMISSIONS CONTROL SYSTEM. THE EMISSION CONTROL SYSTEM INCLUDES PARTICLE TREATMENT AND VOC TREATMENT. THE MAIN SYSTEM INCLUDES THE ADDITION OF A DROP OUT BOX, (2) ABORT GATES (2) VENTURI SCRUBBERS, (2) FANS, (2) REGENERATIVE THERMAL OXIDIZERS AND (2) ACID-GAS SCRUBBERS. SMG SCOPE OF WORK INCLUDES STRUCTURAL SUPPORTS, ACCESS AND FOUNDATIONS FOR THE NEW EQUIPMENT.

GEOTECHNICAL:

- 1. REFER TO THE GEOTECHNICAL REPORT BY GRI.
- 2. FOR DEMOLITION, EXCAVATION AND SUBGRADE PREPARATION REQUIREMENTS SEE GEOTECHNICAL REPORT
- 3. THE DESIGN SAFE BEARING CAPACITY IS ASSUMED TO BE 2,000 PSF WITH SITE CLASS F.

REINFORCED CONCRETE:

- 1. ALL CAST-IN-PLACE CONCRETE SHALL DEVELOP A MINIMUM COMPRESSIVE STRESS OF 4000 PSI AT 28 DAYS. MAXIMUM SLUMP SHALL BE 4 INCHES — UNLESS NOTED OTHERWISE ON THE CONCRETE DRAWINGS.
- 2. CONCRETE SHALL USE TYPE II CEMENT AND MIX DESIGNED WITH A MAXIMUM WATER TO CEMENT RATIO OF 0.45.
- 3. READY-MIXED CONCRETE SHALL BE MIXED AND DELIVERED TO THE JOB SITE IN ACCORDANCE WITH THE REQUIREMENTS SET FORTH IN "SPECIFICATIONS FOR READY-MIXED CONCRETE" (ASTM C94).
- 4. ALL CONCRETE SHALL BE CONSOLIDATED BY SUITABLE MEANS DURING PLACEMENT AND SHALL BE THOROUGHLY WORKED AROUND REINFORCEMENT, EMBEDDED FIXTURES AND INTO CORNERS OF FORMS.
- 5. ALL FORMS TO BE CLEAN, WITH NO WATER OR LOOSE MATERIAL PRESENT.
- 6. DURING HOT WEATHER, PROPER ATTENTION SHALL BE GIVEN TO INGREDIENTS, PRODUCTION METHODS, HANDLING, PLACING, PROTECTION, AND CURING TO PREVENT EXCESSIVE CONCRETE TEMPERATURES OR WATER EVAPORATION THAT MAY IMPAIR REQUIRED STRENGTH OR SERVICEABILITY OF THE MEMBER OR STRUCTURE. REFER TO ACI 305.
- 7. NO CONCRETE ADMIXTURES SHALL BE USED WITHOUT PRIOR APPROVAL OF THE ENGINEER OR AS SPECIFIED IN THESE SPECIFICATIONS.
- 8. ALL EXPOSED CORNERS SHALL HAVE A 3/4" CHAMFER UNLESS NOTED OTHERWISE.
- 9. REINFORCING STEEL AND CONCRETE CONSTRUCTION SHALL CONFORM TO THE "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE" (ACI 318) AND ACI 315.
- 10. ALL PROPOSED COLD JOINTS TO BE REVIEWED BY THE ENGINEER. ALL COLD JOINTS TO BE ROUGHENED AND
- 11. REINFORCING STEEL SHALL CONFORM TO ASTM A615, GRADE 60, FOR DEFORMED BARS.
- 12. BARS IN SLABS SHALL BE SUPPORTED ON WELL-CURED CONCRETE BLOCKS, METAL OR PLASTIC CHAIRS, AS SPECIFIED BY THE CRSI MANUAL OF STANDARD PRACTICE, MSP-1. REINFORCING STEEL SHALL BE DETAILED IN ACCORDANCE WITH THE "ACI MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES," ACI 315. LAP ALL REINFORCING BARS PER THE TYPICAL LAP SPLICE LENGTH SCHEDULE, EXCEPT AS NOTED.
- 13. SPLICE LENGTHS SHALL BE AS SHOWN IN THE FOLLOWING TABLE, UNLESS NOTED OTHERWISE ON THE DRAWINGS:

BAR SIZE	SPLICE LENGTH	BAR SIZE	SPLICE LENGTH	
#4	25 IN.	#10	78 IN.	
#5	31 IN.	" 11	86 IN.	
#6	37 IN.	<i>"</i>		
 #7	54 IN.			
#8	61 IN.			
"				

- 14. BACKFILL MATERIAL SHALL BE AS RECOMMENDED IN BACKFILL NOTES.
- 15. ALL BLOCKOUTS, SLEEVES, OPENINGS, CONDUIT AND OTHER EMBEDDED ITEMS NOT SHOWN ON THE STRUCTURAL DRAWINGS SHALL BE APPROVED BY THE STRUCTURAL ENGINEER BEFORE POURING. CONDUITS EMBEDDED IN SLABS SHALL NOT BE LARGER IN OUTSIDE DIMENSION THAN ONE THIRD OF THE THICKNESS OF THE SLAB AND SHALL NOT BE SPACED CLOSER THAN THREE DIAMETERS ON CENTER. VERIFY ALL BLOCKOUTS WITH MECHANICAL, ELECTRICAL AND PLUMBING REQUIREMENTS.
- 16. CONCRETE COVER REINFORCING STEEL AND OTHER EMBEDDED STEEL SHALL BE AS SHOWN ON DRAWING. IF NOT SHOWN, USE COVERS AS SPECIFIED IN ACI 318, AS NOTED BELOW:

CONCRETE CAST AGAINST EARTH3 INCHES	
CONCRETE EXPOSED TO EARTH OR WEATHER:	
#5 BAR AND SMALLER1 1/2 INCHES	
#6 BAR AND LARGER2 INCHES	
CONCRETE NOT EXPOSED TO EARTH NOR WEATHER:	
SLABS, WALLS, JOINTS3/4 INCH	
BEAMS, COLUMNS1 1/2 INCHES	

17. ELECTRICAL GROUNDING ELEMENTS SHALL BE IN PLACE PRIOR TO POURING CONCRETE.

GROUTING:

- 1. ALL BASE PLATES AND GROUT-POCKETS FOR SHEAR KEYS. SHALL BE GROUTED IN ACCORDANCE WITH AISC 303-05. 2. GROUT SHALL BE PRE-APPROVED BY THE ENGINEER AND SHALL BE HIGH STRENGTH, NON-SHRINK, NON-METALLIC.
- 3. GROUT SHALL BE INSTALLED AND ALL CONTACT SURFACES SHALL BE CLEANED AND PREPARED BEFOREHAND IN ACCORDANCE WITH THE GROUT-SUPPLIER'S SPECIFICATIONS.

STRUCTURAL STEEL:

STRUCTURAL STEEL SHALL CONFORM TO:

ASTM A992	WIDE FLANGE AND TEES
ASTM A36	CHANNELS, PLATES AND ANGLES, EXCEPT AS NOTED.
ASTM A500, GRADE B	HOLLOW STRUCTURAL SECTIONS (TUBES)
ASTM A53, GRADE B	PIPES
ASTM A572 GR 50	PLATES WHERE NOTED IN DRAWINGS

- 1. DESIGN, FABRICATION, AND ERECTION SHALL BE IN ACCORDANCE WITH AISC 360-05 "SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS" WITH "COMMENTARY" AND THE "CODE OF STANDARD PRACTICE", WITH EXCEPTIONS NOTED IN SPECIFICATIONS.
- 2. BOLTS IN PRIMARY STRUCTURAL CONNECTIONS SHALL CONFORM TO ASTM A325.

CEMENTITIOUS OR EPOXY-TYPE - UNLESS NOTED OTHERWISE ON THE DRAWINGS.

- 3. STANDARD STRUCTURAL WASHERS SHALL CONFORM TO ASTM F436.
- 4. ANCHOR RODS SHALL CONFORM TO ASTM F1554 GR 36 UNO ON THE CONCRETE DRAWINGS.
- 5. POST INSTALLED ANCHORS SHALL BE AS SHOWN ON THE DESIGN DRAWINGS BACKED BY REQUIRED ICC TEST REPORTS.
- 6. WELDING SHALL CONFORM TO AWS D1.1 CODE FOR ARC AND GAS WELDING IN BUILDING CONSTRUCTION. WELDING SHALL BE PERFORMED IN ACCORDANCE WITH A WELDING PROCEDURE SPECIFICATION (WPS) AS REQUIRED IN AWS D1.1 AND APPROVED BY THE ENGINEER. THE WPS VARIABLES SHALL BE WITHIN THE PARAMETERS ESTABLISHED BY THE FILLER-METAL MANUFACTURER.
- 7. ALL CONNECTIONS, UNLESS NOTED OTHERWISE, SHALL BE FULLY WELDED CONNECTIONS. FILLET WELD SIZE TO BE 1/16" LESS THAN THE THINNEST MATERIAL WITH A MINIMUM OF 3/16". BUTT WELDS TO BE COMPLETE JOINT PENETRATION (CJP) BUTT OR BEVEL WELDS IN ACCORDANCE WITH AWS.
- 8. WELDS SHALL BE MADE USING E70 ELECTRODES. ALL STRUCTURAL WELDING SHALL BE BY AWS CERTIFIED WELDERS.

CONTRACTOR REQUIREMENTS:

- 1. THE CONTRACTOR SHALL COORDINATE SEISMIC RESTRAINTS OF MECHANICAL, PLUMBING AND ELECTRICAL EQUIPMENT, MACHINERY, AND ASSOCIATED PIPING WITH THE STRUCTURE.
- 2. FIELD ENGINEERED DETAILS DEVELOPED BY THE CONTRACTOR THAT DIFFER FROM OR ADD TO THE STRUCTURAL DRAWINGS SHALL BEAR THE SEAL AND SIGNATURE OF A STRUCTURAL ENGINEER REGISTERED IN CALIFORNIA AND SHALL BE SUBMITTED TO THE EOR PRIOR TO CONSTRUCTION.
- 3. THE GENERAL INSTALLATION CONTRACTOR SHALL VERIFY ALL DIMENSIONS AT THE SITE. ALL DISCREPANCIES SHALL BE CALLED TO THE ATTENTION OF THE ENGINEER AND BE RESOLVED PRIOR TO PROCEEDING WITH THE WORK.
- 4. THE CONTRACTOR IS TO PROVIDE BARRICADES, SIGNS, LIGHTS OR OTHER DEVICES AROUND THE WORK SITE AS REQUIRED AND/OR AS DIRECTED BY SAFETY PERSONAL.
- 5. LOCATION OF EXISTING UNDERGROUND UTILITIES ARE NOT CLEARLY KNOWN; CONTRACTOR TO TAKE CARE WITH EXCAVATIONS AND CONSTRUCTION.
- 6. ALL MATERIAL AND WORKMANSHIP TO CONFORM TO APPROPRIATE CODES AND STANDARDS.
- 7. THE CURRENT EDITION OF ALL REFERENCED CODES, STANDARDS AND SPECIFICATIONS SHALL GOVERN.
- 8. THE CONTRACTOR SHALL COMPLY WITH CALIFORNIA-OSHA GUIDELINES, BE RESPONSIBLE FOR ALL CONSTRUCTION METHODS, TEMPORARY SHORING, BRACING, TECHNIQUES, SEQUENCING AND SAFETY REQUIRED FOR CONSTRUCTION.
- 9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR STABILITY OF THE STRUCTURE DURING CONSTRUCTION. THE
- STRUCTURE SHOWN IN GENERAL ARRANGEMENT DRAWINGS IS STABLE IN THE COMPLETED CONFIGURATION ONLY.

PAINT COATINGS:

1ALL NEW STRUCTURAL STEEL SHALL BE PREPARED AND COATED IN ACCORDANCE WITH THE SSPC AND OWNER'S FINAL APPROVAL OF COLORS AS SPECIFIED. THIRD PARTY PAINT THICKNESS TESTING, MAY BE REQUIRED TO BE DONE PER DISCRETION OF OWNER'S PROJECT REPRESENTATIVE.

GENERAL: ALL NEW STRUCTURAL STEEL SHALL RECEIVE SSPC-SP6 COMMERCIAL SANDBLAST ON ALL EXPOSED SURFACES. MINIMUM ACCEPTABLE SURFACE PREPARATION TO BE: POWER TOOL CLEANING (SSPC-SP3) WHICH INCLUDES SOLVENT CLEANING (SSPC-SP1).

ALL EXPOSED STEEL SURFACES:

DO NOT PAINT AREAS TO BE FIELD WELDED.

PRIMER: APPLY (1) COAT OF "WASSER MC-ZINC 100" - 4.0MILS [MIN] DRY FILM THICKNESS. TOP COAT: APPLY (1) COAT OF "WASSER MC-FERROX A" - 4.0MILS [MIN] DRY FILM THICKNESS

- ALL STRUCTURAL AND FABRICATED PLATE COMPONENTS: COLOR TO BE GRAY TO MATCH EXISTING STEELWORK AND PER OWNER'S PRE-APPROVAL].

- ALL GUARDRAILS, LADDERS, STAIR NOZING AND LIFT LUGS: COLOR TO BE OSHA SAFETY YELLOW WELD-DISTURBED AREAS: AFTER FIELD WELDING AND FOR FIELD TOUCH-UP OF PAINTED SURFACES: PREP AFFECTED AREAS WITH SSPC-SP2-3, HAND CLEAN OR POWER TOOL, AND APPLY THE APPLICABLE COATING SYSTEM

SUBMITTALS:


AS OUTLINED ABOVE.

SHOP DRAWINGS SHALL BE SUBMITTED TO THE ENGINEER OF RECORD (EOR) AND REVIEWED PRIOR TO FABRICATION AND CONSTRUCTION REGARDING ALL STRUCTURAL ITEMS

AS NOTED

1. ANY CHANGES TO THE STRUCTURAL DRAWINGS SHALL BE SUBMITTED TO THE EOR AND ARE SUBJECT TO REVIEW AND ACCEPTANCE BY THE EOR.

IS DRAWING, INCLUDING THE PRINCIPLES DESIGN IS THE PROPERTY OF SMG INC. E DESIGN SHOWN IN THIS DRAWING IS TE SPECIFIC AND SHALL BE USED ONLY R THE PROJECT SHOWN ON THE TITLE OCK. IF THIS DRAWING IS NOT STAMPED ITH AN ENGINEER'S SEAL, THE DRAWING Y HAVE BEEN REPRODUCED FROM AN IAUTHORIZED COPY. AUTHORIZED INTROL DOCUMENT IS EITHER A STAMPED RD COPY OR DIGITALLY PROTECTED RIGINAL. THIS DRAWING SHALL NOT BE ED IN A MANNER THAT WOULD BE A TRIMENT TO SMG. ACCEPTANCE OF THIS AWING IS AN AGREEMENT TO THE ABOVE.					
	0	ISSUED FOR PERMIT	JL	01/17/22	JW
	SYM.	REVISIONS	BY	DATE	снк,





6/18/21

J.D. WALLACE

8625 SW Cascade Ave. Suite 600 Beaverton, Oregon 97008 Phone: 503.643.8595 Fax: 503.643.8610 www.smgengr.com

SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY NEW SHREDDER ENCLOSURE AND AIR CONTROL

GENERAL NOTES

19-029F-G02

GENERAL DESIGN CRITERIA

STRUCTURAL DESIGN WAS BASED ON THE STRENGTH AND DEFLECTION CRITERIA OF THE 2018 IBC AND 2019 OSSC MODIFICATIONS. IN ADDITION TO THE SELF-WEIGHT OF THE STRUCTURAL ELEMENTS, THE FOLLOWING LOADS AND CRITERIA WERE USED:

DESIGN LOADS:

RISK CATEGORY II

<u>DEAD LOAD</u>

ACTUAL WEIGHT OF MATERIALS OF CONSTRUCTION AND PERMANENT EQUIPMENT

LIVE LOAD

ROOF DECK 25 PSF UNIFORM

ACCESS PLATFORM [D.O.B.]

60 PSF UNIFORM 1,000 LB CONCENTRATED

ELEVATED WALKWAY

40 PSF UNIFORM 1,000 LB CONCENTRATED

STAIRS AND LANDINGS

100 PSF UNIFORM 1,000 LB CONCENTRATED

FALL ARREST TIE-OFF POST:

2,250LB

SNOW LOAD
SNOW IMPORTANCE FACTOR, ls = 1.0

10 PSF GROUND SNOW LOAD ROOF SNOW LOAD

25 PSF (INCLUDED 5 PSF RAIN SURCHARGE)

WIND LOAD

BASIC WIND SPEED (3-SECOND GUST), V=96 MPH WIND IMPORTANCE FACTOR, lw = 1.0

EXPOSURE

SEISMIC LOAD SEISMIC IMPORTANCE FACTOR, le = 1.0

[PER GEOTECHNICAL INVESTIGATION REPORT BY GRI, ISSUED 3/23/2021.]

SITE CLASS

MAPPED SPECTRAL RESPONSE ACCELERATION

SHORT PERIOD, Ss 1 SECOND PERIOD, S1 0.41g

SPECTRAL RESPONSE COEFFICIENTS

SHORT PERIOD, Sds 0.54 1 SECOND PERIOD, Sd1 1.09

SEISMIC DESIGN CATEGORY

SOIL LOAD BEARING PER GEOTECHNICAL INVESTIGATION REPORT BY GRI, ISSUED 3/23/2021.

ALLOWABLE BEARING PRESSURE

2,000 PSF LONG TERM LOADS 2,666 PSF SHORT TERM LOADS

32.4 FT

FLOOD LOAD (FOR EQUIPMENT AND STRUCTURES BELOW EL. 34.5 FT, NAVD88)

<u>COP</u> 28.9 FT BASE 100 YEAR FLOOD ELEVATION 1996 FLOOD INUNDATION ELEVATION 32.5 FT 30.4 FT

FLOOD PROTECTION ELEVATION (2 FT FREEBOARD) 34.5 FT BUOYANCY FORCE (DISPLACED VOLUME) 62.4 PCF

62.4 PCF HYDROSTATIC PRESSURE

LOAD COMBINATIONS:

APPLICABLE FACTORS AS LISTED IN ASCE 7-16

EQUIPMENT ENCLOSURES & SUPPORTS: SPECIFIC SEISMIC DESIGN CRITERIA

THE FOLLOWING LATERAL FORCE RESISTING SYSTEMS, RESPONSE MODIFICATION COEFFICIENTS AND LATERAL DESIGN FACTORS ARE APPLICABLE TO THE DESIGN OF EQUIPMENT ENCLOSURES & SUPPORT STRUCTURES, IN ACCORDANCE WITH 2019 OSSC (REF. ASCE7-16 AND SEISMIC DESIGN MANUAL).

SHREDDER ENCLOSURE:

OCBF 2.5

DUCT & WALKWAY SUPPORT BENTS:

OCBF [TRUSSED TOWER]

DROP OUT BOX [DOB] SUPPORT STRUCTURE:

LRFS OCBF [TRUSSED TOWER]

0.24

<u>VENTURI-SCRUBBERS' AND OUTLET DUCT SUPPORT STRUCTURES:</u>

OCBF 2.5 0.24

REGENERATIVE THERMAL OXIDIZER [RTO] SUPPORT STRUCTURE:

OCBF 2.5 0.24

ACID GAS SCRUBBERS' [AGS] SUPPORT STRUCTURE:

2.5 0.24

COMPRESSOR ROOM:

OCBF[E/W] OMF [N/S] LRFS 3.25 0.19

POWER DISTRIBUTION CENTER [PDC] SUPPORT FOOTING:

2.5 Cs[EFFECTIVE] 0.31





J.D. WALLACE

8625 SW Cascade Ave. Suite 600

Beaverton, Oregon 97008 Phone: 503.643.8595 Fax: 503.643.8610

www.smgengr.com

SCHNITZER STEEL INDUSTRIES, INC. PORTLAND FACILITY

NEW SHREDDER ENCLOSURE AND AIR CONTROL

GENERAL NOTES

19-029F-G03 AS NOTED 6/18/21


THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC. THE DESIGN SHOWN IN THIS DRAWING IS SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE BLOCK. IF THIS DRAWING IS NOT STAMPED WITH AN ENGINEER'S SEAL, THE DRAWING MAY HAVE BEEN REPRODUCED FROM AN UNAUTHORIZED COPY. AUTHORIZED CONTROL DOCUMENT IS EITHER A STAMPED HARD COPY OR DIGITALLY PROTECTED ORIGINAL. THIS DRAWING SHALL NOT BE USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS


0 ISSUED FOR PERMIT


REVISIONS


DRAWING IS AN AGREEMENT TO THE ABOVE.


| JL | 01/17/22 | JWC BY DATE CHK'D


























A NORTH ELEVATION @ AGS & VENTURI SCRUBBER S04 1/8" = 1'-0"



B SOUTH ELEVATION @ RTO, COMPRESSOR ROOM & PDC SO4 1/8" = 1'-0"





Smith Monroe Gray
ENGINEERS, INC.

Phone: 503,643,8595
Fax: 503,643,8610

DRAWN BY
J. LUM

PATE

CHKD BY

B8625 SW Cascade Ave.
Suite 600
Beaverton, Oregon 97008
Beaverton, Oregon 97008

Phone: 503,643,8595
Fax: 503,643,8610


NEW SHREDDER ENCLOSURE AND AIR CONTROL


NEW FOUNDATION LAYOUT


REV.
AS NOTED


REV.
AS NOTED

19-029F-S05









THIS DRAWING, INCLUDING THE PRINCIPLES OF DESIGN IS THE PROPERTY OF SMG INC. THE DESIGN SHOWN IN THIS DRAWING IS SITE SPECIFIC AND SHALL BE USED ONLY FOR THE PROJECT SHOWN ON THE TITLE BLOCK. IF THIS DRAWING IS NOT STAMPED 8625 SW Cascade Ave. Suite 600 Beaverton, Oregon 97008 SCHNITZER STEEL INDUSTRIES, INC.

PORTLAND FACILITY

NEW SHREDDER ENCLOSURE AND AIR CONTROL Smith Monroe Gray WITH AN ENGINEER'S SEAL, THE DRAWING
MAY HAVE BEEN REPRODUCED FROM AN
UNAUTHORIZED COPY. AUTHORIZED
CONTROL DOCUMENT IS EITHER A STAMPED
HARD COPY OR DIGITALLY PROTECTED Phone: 503.643.8595 Fax: 503.643.8610 ENGINEERS, INC. ELEVATIONS - NEW SCHREDDER ENCLOSURE www.smgengr.com ORIGINAL. THIS DRAWING SHALL NOT BE DRAWN BY USED IN A MANNER THAT WOULD BE A DETRIMENT TO SMG. ACCEPTANCE OF THIS DRAWING IS AN AGREEMENT TO THE ABOVE. J.D. WALLACE 7/27/21 19-029F-S12 0
 JL
 01/17/22
 JWC

 BY
 DATE
 CHK'D
 AS NOTED O ISSUED FOR PERMIT EXPIRES: 12-31-23 REVISIONS

