

CHAPTER 24.50 - FLOOD HAZARD AREAS

Sections:

- 24.50.010 Purpose.
- 24.50.020 General.
- 24.50.030 Flood Related Definitions.
- 24.50.040 Flood Insurance Administration Study and Flood Hazard Maps.
- 24.50.050 Flood Hazard Areas and Flood Protection Elevations.
- 24.50.060 Provisions for Flood Hazard Reduction.
- 24.50.065 Recreational Vehicles located in Areas of Special Flood Hazard or Base Flood Zones.
- 24.50.070 Appeals and Variances.

24.50.010 Purpose.

The purpose of this Chapter is to ~~protect~~promote the public health, safety, and general welfare ~~by restricting or prohibiting uses which are dangerous to health, safety, or property in times of flood or which cause increased flood heights or velocities, and by requiring that uses to minimize public and structures vulnerable private losses due to floods be protected from flood danger at the time of initial construction~~flooding in flood hazard areas.

24.50.020 General.

- A. ~~The provisions of this Chapter shall regulate~~All development and construction within flood hazard areas, as defined identified in Section 24.50.030, are subject to the terms of this Chapter and all other applicable regulations.
- B. ~~Land classified in a flood hazard area may restrict or affect uses and development permitted in one or more of the regular zones listed in Chapter 33.16. If an inconsistency or conflict exists between Chapter 24.50 and other titles provisions of this Code, including Title 33, the more restrictive uses or requirements shall prevail will apply.~~
- C. A structure or ~~the use of a structure or property which~~that was lawful ~~before the original date of this Chapter~~when it was established or approved by the City, but which is that ~~does not in conformity~~conform with the current provisions of this Chapter may be continued subject to the provisions of the State Building Code; ~~regulations for pertaining to~~ existing structures.
- D. The flood protection elevations and the floodway and floodway fringe areas specified by this Chapter, based on the 100-year flood elevations and the February 1996 Flood Inundation Area, as described in the Composite February 1996 Flood Inundation Area Mapping described in Subsection 24.50.040 E. below, are considered reasonable for regulatory purposes. Greater flood heights and more extensive floodway fringe areas associated with climate change and larger longer floods ~~frequency occurrences~~ may occur or the flood height and extent of flooding may be increased by human or natural causes, such as log jams, bridge openings or culverts restricted by debris, or changes in basin conditions. Areas within

designated drainage districts and those areas not covered by adequate topographic maps may contain unmapped watercourses subject to flooding. The identification of designated flood hazard areas does not imply that lands outside of such areas will be free from flooding or flood damage.

The City of Portland, ~~or~~ any officer or employee thereof, ~~or~~ and the Federal Insurance Administration ~~shall~~ will not be liable for any flood damages that result from reliance on the provisions or designations of this Chapter or any administrative decision lawfully made thereunder.

- E. The Bureau of Development Services administers and enforces the State of Oregon Specialty Codes, as adopted in Chapter 24.10, which contain certain provisions that apply to the design and construction of buildings and structures located in flood hazard areas, as defined in this Chapter. This Chapter will be administered and enforced in conjunction with such Specialty Codes.
- F. The Director of the Bureau of Development Services will appoint a Floodplain Administrator who will be responsible for administering, implementing, and enforcing this Chapter, including granting or denying development permits in accordance with its provisions. The Floodplain Administrator may delegate authority to implement these provisions.

24.50.030 Flood Related Definitions.

The definitions contained in this Section relate to flood hazard areas and considerations outlined in this Chapter.

- A. "Appeal" means a request for a review of the City of Portland's interpretation of any provision of this ~~ordinance~~ Chapter or a request for a variance.
- B. "Area of shallow flooding" means a designated AO or AH zone on the Flood Insurance Rate Map (FIRM). The base flood depths range from 1 to 3 feet; a clearly defined channel does not exist; the path of flooding is unpredictable and indeterminate; and, velocity flow may be evident. AO is characterized as sheet flow and AH indicates ponding.
- C. "Areas of Special Flood Hazard" mean the land in the flood plain ~~within a community~~ subject to a one percent or greater chance of flooding in any given year. Designation on Flood Insurance Rate Maps always includes the letters A or V. "Special flood hazard area" is synonymous with the phrase "area of special flood hazard."
- D. "Base Flood (100-year flood)" means the flood having 1 percent chance of being equaled or exceeded in any given year. ~~Designation on maps always includes the letters A or V.~~
- E. "Base flood elevation (BFE)" means the elevation to which floodwater is anticipated to rise during the base flood.

Exhibit A

- EF.** “Basement” means any area of the building having its floor, including crawlspace, subgrade (below ground level) on all sides.
- G.** “Building” – See Structure.
- FH.** "City Datum" means the reference datum for the City of Portland maps. The FIRM maps described in Section 24.50.050 are referenced to the North American Vertical Datum (NAVD) of 1988. To convert NAVD 1988 level to City datum, subtract 2.125 feet from the elevation referenced to NAVD 1988 level.
- I.** “Design Flood” means the greater of the base flood or the February 1996 Flood Inundation Area.
- J.** “Design Flood Elevation” means the greater of the base flood elevation or the February 1996 Flood Inundation Area elevation.
- GK.** "Development" means any ~~man-made~~human-created change to improved or unimproved real estate, including but not limited to buildings, bridges, other structures, and mining, dredging, filling, grading, paving, excavation, fencing, landscaping, drainage facilities, drilling operations, or storage of equipment or material.
- HL.** "Existing manufactured home park or manufactured home subdivision" means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale for which the construction of facilities for servicing the lot on which the manufactured home is to be affixed (including as a minimum, the installation of utilities, either final site grading or the pouring of concrete pads, and the construction of streets) is completed before ~~the original date of this Chapter~~October 18, 1979.
- IM.** "Expansion to an existing manufactured home park or manufactured home Subdivision" means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, either final site grading or the pouring of concrete pads, and the construction of streets).
- JN.** "FIA" means the Federal Insurance Administration.
- KO.** "Flood Hazard Area" means any area ~~which~~that has been identified as subject to flooding.
- LP.** “Flood Insurance Study” means the official report provided by the Federal Insurance Administration that contains information regarding flooding, discusses the engineering methods used to develop the Flood Insurance Rate Maps (FIRMs), and includes flood profiles, and the water surface elevation of the base flood.
- MQ.** "Flood Insurance Rate Map (FIRM)" means the official map on which the Federal Insurance Administration has delineated the areas of special flood hazards.

Exhibit A

- NR.** "Flood or flooding" means a general and temporary condition of partial or complete inundation of normally dry land areas from the overflow of inland or tidal waters, ~~and~~ or the unusual and rapid accumulation of runoff of surface waters from any source.
- OS.** "Flood protection elevation" means the ~~water surface~~ design flood elevation ~~of the base flood~~ plus a freeboard allowance.
- PT.** "Floodplain" means the channel of watercourse and adjacent land areas ~~which~~ that are subject to inundation by the ~~base~~ design flood.
- U.** "Floodplain Administrator" means the City of Portland official designated by the Director of the Bureau of Development Services to administer and enforce this Chapter.
- QV.** "Floodproofing" means any combination of structural and nonstructural additions, changes, or adjustments to structures ~~which~~ that reduce or eliminate the risk of flood damage to real estate or improved real property, sanitary, and water facilities, structures, and their contents. Floodproofed structures are those that have the structural integrity and design to be watertight with walls substantially impermeable to the passage of water.
- RW.** "Floodway" means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than ~~one foot~~ a designated height. The actual floodway boundaries are computer ~~activated~~ generated and approximate. These boundaries are depicted on the FIRM. Boundaries for other watercourses may be subject to identification by the Sewage System Administrator. The width of the floodway for unidentified watercourses ~~should~~ may not be less than 15 feet unless otherwise approved by the Sewage System Administrator.
- SX.** "Flood fringe area" means any area lying outside the floodway ~~which~~ that is subject to flooding by a base flood and for which water surface elevations and floodway and flood fringe boundaries have been determined by a Flood Insurance Study and are shown on the FIRMs. Boundaries for unidentified watercourses may be subject to identification by the Sewage System Administrator.
- FY.** "Freeboard" means an additional height above the ~~base~~ design flood ~~level~~ elevation to account for factors that may contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as filling in the floodway fringe, wave action, effect of urbanization of the watershed, map inaccuracies, irregular ~~stream~~ watercourse cross sections, irregular constructions at bridges, and the uncertainties of flood discharge computations.
- UZ.** "Lowest Floor" means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood-resistant enclosure, usable solely for parking of vehicles, building access, or storage, in an area other than a basement area, is not considered a building's lowest floor, provided that such enclosure is not built so as

to render the structure in violation of the applicable non-elevation design requirements of ~~this ordinance found at~~ Subsection 24.50.060 F.2.

- ~~V~~AA. "Manufactured home" means a structure transportable in one or more sections, ~~which that~~ is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. For flood-plain management purposes, the term "manufactured home" also includes park trailers, travel trailers, and other similar vehicles placed on a site for greater than 180 consecutive days. For insurance purposes, the term "manufactured home" does not include park trailers, travel trailers, and other similar vehicles.
- ~~W~~BB. "New construction" means structures for which the start of construction commenced on or after ~~the effective date of this Chapter~~ October 18, 1979.
- ~~X~~CC. "New manufactured home park or manufactured home subdivision" means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale for which the construction of facilities for servicing the lots on which the manufactured home is to be affixed (including as a minimum, the installation of utilities, either final site grading or the pouring of concrete pads and the construction of streets) is completed on or after ~~the original date of this Chapter~~ October 18, 1979.
- DD. "Reasonably safe from flooding" means floodwaters and subsurface waters related to the design flood or other sources identified by the Sewage System Administrator will not damage proposed or existing structures.
- EE. "Sewage System Administrator" means the person designated by the Bureau of Environmental Services who is responsible for regulating the public sanitary and stormwater facilities. The Sewage System Administrator may delegate their authority for the purpose of implementing these provisions.
- ~~Y~~FF. "Start of construction" ~~includes substantial improvement, and~~ means the date the building permit was issued, provided the actual ~~start of~~ construction, repair, reconstruction, substantial improvement, placement, or other improvement was commenced within 180 days of the permit issuance date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading, or and filling; ~~nor does it include~~ the installation of streets, walkways, sanitary sewers, storm sewers, ~~and/or~~ drainage facilities; ~~nor does it include~~ excavation for a basement, footings, piers, or a foundation or the erection of temporary forms; ~~nor does it include~~ or the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure.

ZGG. “Structure or accessory structure” means, ~~for the purposes of this Chapter,~~ a walled and roofed building, including a gas or liquid storage tank, ~~that is principally above ground~~ as well as a manufactured home.

AAHH. “Substantial Damage” means damage of any origin sustained by a structure whereby the cost of restoring the structure to its ~~before-pre-~~damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

BBII. "Substantial Improvement" means any repair, reconstruction, or improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure, either:

1. Before the start of construction of the improvement or repair is started, or
2. If the structure has been damaged, and is being restored, before the damage occurred. Substantial improvement is considered to occur when the first alteration of any wall, ceiling, floor, or other structural part of the building commences, whether or not that alteration affects the external dimensions of the structure.

The term does not, however, include either:

- a. Any project for improvement of a structure to comply with existing State or local health, sanitary, or safety code specifications ~~that~~which are solely necessary to assure safe living conditions; or
- b. Any alteration of a structure listed on the National Register of Historic Places or the State Inventory of Historic Places.

CCJJ. “Variance” means a grant of relief from the requirements of this ~~ordinance~~ which Chapter that permits construction in a manner that would otherwise not be prohibited by allowed under this ordinance Chapter.

DDKK. “Water surface elevation” means the height of the water surface of the ~~design~~base flood for any point along the longitudinal course of a ~~stream~~watercourse.

EELL. “Watercourse” means a channel in which a flow of water occurs, either continuously or intermittently, and if the latter, with some degree of regularity. Watercourses may be either natural or artificial.

24.50.040 FIA Flood Insurance Administration Study and Flood Hazard Maps.

The following study and maps in this Section are hereby adopted and declared to be a part of this Chapter.

- A. Flood Insurance Study is the official scientific and engineering report entitled “Flood Insurance Study for City of Portland, Oregon: Multnomah, Clackamas and

Washington Counties,” dated November 26, 2010, prepared by the Federal Insurance Administration (FIA) under agency agreement with the Portland District Corps of Engineers. The latest edition of the report, along with accompanying FIRMs, are on file with the Bureau of Development Services.

- B. Flood Insurance Rate Maps (FIRMs) are the official maps entitled “The Flood Insurance Rate Maps (FIRMs) for City of Portland, Oregon: Multnomah, Clackamas and Washington Counties,” dated either October 19, 2004, or November 26, 2010, whichever is more current, on which the Federal Insurance Administration has delineated the areas of flood hazards along with the 100-year (base flood) and 500-year flood boundaries, the floodway zone boundaries and the 100-year flood elevations.
- C. ~~Water Features Map is the official map, dated May, 1981, or latest edition, compiled by the Bureau of Planning and Sustainability delineating certain watercourses which are subject to special flood hazard and drain 30 acres or more. Other Flood Insurance Studies and Flood Insurance Rate Maps for areas within jurisdictions subject to Chapter 24.50 under separate intergovernmental agreements.~~
- D. When base flood elevation data has not been provided by the FIA study, the Sewage System Administrator may obtain, review, and reasonably utilize any base flood elevation and floodway data available from a federal, state, or other source. This data ~~shall~~will be utilized only after technical review and approval ~~of~~by the Sewage System Administrator.
- E. ~~The “Title 3 Water Quality and Flood Management Area Map,” as adopted by Metro Council on June 18, 1998, is the official map which identifies areas as “Composite February 1996 Flood Inundation Area Mapping” published by the City.”~~ The identified areas are subject to the regulations of this Title.

24.50.050 Flood Hazard Areas and Flood Protection Elevations.

Flood hazard areas ~~shall~~ contain all lands located within the ~~F~~floodway boundary, ~~F~~flood ~~Z~~zones within the ~~F~~flood fringe areas, and other identified ~~F~~flood ~~Z~~zones. Identified ~~Flood~~ ~~Zones~~ are depicted on the ~~National Flood Insurance Rate Map (FIRM).~~ Both identified and unidentified ~~F~~flood ~~H~~azard areas ~~along with~~and flood protection elevations are described in this Section. When a structure is partially located in a flood hazard area, the entire structure is subject to the following. Figure 1 illustrates requirements for new construction, substantial improvements, and substantial damage. When a structure is located within multiple flood zones, the basemore restrictive flood hazard areas and zone elevations apply.

(See Figure 1 at the end of Title 24)

- A. Columbia River FIRM Flood Zone AE. These flood zones represent areas for which base flood elevations are determined. The flood protection elevation ~~shall~~ be the base flood elevation plus ~~one~~one foot of freeboard. The nominal ~~one~~one-foot increase for freeboard reflects the relatively wide flood-plain of the Columbia River.

Exhibit A

In the vicinity of the confluence of the Columbia and Willamette Rivers, the Columbia River floodplain ~~shall be~~ considered to be east of the westerly floodway fringe boundary of the Columbia Slough.

- B.** Multnomah Drainage District No. 1, Peninsula Drainage District No. 1, and Peninsula Drainage District No. 2 FIRM Flood Zones AH and A. FIRM Flood Zone AH. ~~This flood zone~~ represents isolated areas of shallow flooding (1 to 3 feet in depth, resulting from upslope runoff) for which base flood elevations are determined. FIRM Flood Zone A represents areas for which base flood elevations are not determined. In the case of unidentified watercourses occurring within the boundaries of the Drainage Districts, the base flood elevation ~~shall~~ will be estimated by procedures described in ~~paragraph~~ Subsection G. below. The flood protection elevation ~~shall be~~ the base flood elevations plus ~~one~~ one foot of freeboard.
- C.** Columbia River FIRM Flood Zone A. These flood zones represent areas for which base flood elevations are not determined. The flood protection elevation ~~shall be~~ either the grade at the adjacent flood fringe boundary or the crown of the nearest street, whichever is higher, plus ~~one~~ one foot of freeboard.
- D.** Willamette River FIRM Flood Zone AE. These flood zones represent areas for which the base flood elevations are determined. The flood protection elevation ~~shall be~~ the base flood elevation plus ~~two~~ two feet of freeboard.
- E.** Johnson Creek, Fanno Creek and Crystal Springs Creek FIRM Flood Zone AE. This flood zone represents areas for which the base flood elevations are determined. The flood protection elevation ~~shall be~~ the base flood elevation plus ~~two~~ two feet of freeboard.
- F.** Johnson Creek FIRM Flood Zone AH. This flood zone represents areas of shallow flooding depth (1 to 3 feet) for which base flood elevations are determined. The flood protection elevation ~~shall be~~ the base flood elevation plus ~~two~~ two feet of freeboard.
- G.** Johnson Creek FIRM Flood Zone AO. This flood zone represents areas of shallow flooding depth (1 to 3 feet) for which the depths of flooding are determined. The flood protection elevation ~~shall be~~ the depth of flooding shown on the FIRM map plus ~~two~~ two feet of freeboard above the highest adjacent grade.
- H.** Johnson Creek, Fanno Creek, Tryon Creek, and Crystal Springs Creek FIRM Flood Zone A. These flood zones represent areas for which base flood elevations are not determined. The flood protection elevation ~~shall be~~ the base flood elevation plus ~~two~~ two feet of freeboard. Base flood elevations ~~shall~~ will be calculated in accordance with ~~paragraph~~ Subsection I. below.
- I.** Unidentified Watercourse Flood Zones. These watercourses, generally draining one acre or more, are not identified in a Federal Insurance Study ~~and may not be identified on the Water Features map~~. The flood protection elevation ~~shall be~~ the base flood elevation plus ~~two~~ two feet of freeboard. The width of the floodway

~~shall~~ may not be less than 15 feet, unless otherwise approved by the Sewage System Administrator. The floodway boundary, flood fringe boundary, and flood protection elevation data ~~shall~~ will be based upon watercourse geometry, slope, channel roughness, effect of obstructions, backwater and other factors ~~which~~ that affect flood flow. The requisite flood hazard data, maps, and sections ~~shall~~ must be obtained and developed by procedures approved by the Sewage System Administrator. When appropriate and necessary data are available, the flood protection elevation and floodway and ~~flooding~~ flood fringe boundary data may be provided by the Sewage System Administrator. If pertinent hydrologic data and topographic data are not available, inaccurate, or outdated, and where substantial alterations or relocations of a watercourse are involved, the Sewage System Administrator may require the permit applicant to secure a registered engineer and surveyor to develop and supply the requisite flood hazard data, maps, and sections.

- J. ~~Metro February 1996 Flood Management~~ Inundation Areas. ~~Flood 1996 inundation areas shown on Metro Title 3 Water Quality and Flood Management Area Maps~~ shall must have a flood protection elevation ~~which~~ that provides a minimum of 2 to two feet of freeboard above the ~~Flood February 1996 level.~~ Flood Inundation Elevation. February 1996 Flood Inundation Areas adjacent to Columbia River FIRM Flood Zone AE, Multnomah Drainage District No. 1, Peninsula Drainage District No. 1, Peninsula Drainage District No. 2 Firm Zone AH, and Columbia River FIRM Flood Zone A ~~shall~~ must have a minimum freeboard of 1 foot. The February 1996 Flood Inundation Elevations must be determined using an approved method such as river gage data; high water marks recorded during the flood; data from state, local, or other authorities; inundation area elevation contour interpolation; or a technical analysis stamped by a professional engineer licensed in the State of Oregon and approved by the Sewage System Administrator.

24.50.060 Provisions for Flood Hazard Reduction.

In all flood hazard areas defined in Section 24.50.050, the following ~~provisions are required~~ requirements apply:

- A. Permits. All permit applications ~~shall~~ will be reviewed to determine whether proposed development and building sites comply with the provisions of this Chapter and will be reasonably safe from flooding. A development or building permit ~~shall~~ must be obtained before construction or development begins within any ~~area of flood hazard area.~~ The development or building permit is required for all structures, including manufactured homes, and for all other development, as defined in this Chapter, including fill. Such applications for permits ~~shall~~ must include the following ~~specific~~ information:
1. Boundary of flood hazard areas.
 2. The base flood elevation and design flood elevation.
 3. Elevation of lowest floor, including basement, for all structures and floodproofed elevations for nonresidential structures.

- ~~4.~~ 4. When required by the Floodplain Administrator, documentation necessary to verify substantial improvement or substantial damage.
 - ~~25.~~ 25. Elevation of lowest point of bridge structures.
 - ~~36.~~ 36. Existing and proposed topography of the site taken at a contour interval (normally 1 foot) sufficiently detailed to define the topography over the entire site and adjacent watercourses subject to flooding. Ninety percent of the contours ~~shall~~must be plotted within 1 contour interval of the true location.
 - ~~47.~~ 47. All necessary permits obtained from the federal and state governmental agencies from which prior approval is required.
 - ~~58.~~ 58. Where elevation data is not available either through the Flood Insurance Study or from another authoritative source (see Subsection 24.50.050 G.I.), applications for building permits ~~shall~~will be reviewed to assure that proposed construction will be reasonably safe from flooding. The test of reasonableness is a local judgment and includes use of any available hydrological data, drainage basin hydrology, historical data, high water marks, photographs of past flooding, etc., where available. Failure to elevate at least ~~two~~2 feet above grade in these zones may result in higher insurance rates.
- B.** Elevation reference. The survey reference datum for finished lowest floor including basement, floodproofed elevations, and finished site grades ~~shall~~must be either the North American Vertical Datum of 1988 or City of Portland datum, whichever is appropriate. When approved by the City Engineer, a local onsite survey reference datum may be adopted for FIRM Zones A and Unidentified Watercourse Flood Zones. The survey reference datum ~~shall~~must be indicated on all relevant plan and ~~S~~section drawings, calculations, and the certified ~~Flood-FEMA~~ Elevation Certificate.
- C.** Certification of elevations and floodproofing.
- ~~1.~~ 1. All ~~finished~~ elevations as specified ~~hereunder shall~~below must be certified on a FEMA (FIA) Elevation Certificate by a licensed surveyor or engineer secured by the permittee; and made part of the permit records.
 - ~~1a.~~ 1a. ~~As-built~~During construction elevations of the lowest floor, including basement, of all new or substantially improved structures upon placement of the lowest floor but prior to further vertical construction;
 - ~~2b.~~ 2b. As-built finished elevation of lowest floor including basement of all new or substantially improved structures;

- c. As-built finished floodproofed elevation of all new or substantially improved nonresidential structures;
- 3d. As-graded finished elevation of lowest grade within 25 feet of structures; and
- 4e. As-graded finished elevation of lowest crawl space grade, as applicable.

2. All floodproofing materials and methods for nonresidential structures shall ~~must~~ be certified by a licensed professional engineer or architect as meeting the criteria in Subsection 24.50.060 F.7.

D. Floodway. Encroachments into the floodway by development and structures defined in Section 24.50.020030 are prohibited unless it is demonstrated by technical analysis from a registered engineer that the development will result in no increase in the base flood elevation. In areas where a regulatory floodway has not been designated, no new construction, substantial improvement or other development (including fill) ~~shall~~ will be permitted within Zone AE, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than 1 foot at any point within the ~~community~~ flood hazard areas regulated by the City. Technical analysis ~~shall~~ will be reviewed and approved by the Sewage System Administrator. However, the minimum width of the floodway shall not be less than 15 feet, unless otherwise approved by the Sewage System Administrator.

E. ~~Alteration of watercourses~~ New Technical Data and Notifications of Other Entities. The Bureau of Development Services ~~shall~~ will:

- 1. City Boundary Alterations. Notify the Federal Insurance Administration in writing whenever the boundaries of the City have been modified by annexation or the City has otherwise assumed authority or no longer has authority to adopt and enforce floodplain management regulations for a particular area, to ensure that all Flood Hazard Boundary Maps (FHBM) and Flood Insurance Rate Maps (FIRM) accurately represent the City's boundaries. The Bureau will include within such notification a copy of a map of the City suitable for reproduction, clearly delineating the new corporate limits or new area for which the City has assumed or relinquished floodplain management regulatory authority.
- 2. Watercourse Alterations. Notify adjacent communities, and the Department of Land Conservation and Development, and other appropriate state and federal agencies, prior to any alteration or relocation of a watercourse as identified in the Flood Insurance Study and Flood Insurance Rate Map, and submit evidence of such notification to the Federal Insurance Administration. The applicant must provide this notification to the Federal

Insurance Administration as a Conditional Letter of Map Revision (CLOMR) along with either:

- ~~2a.~~ Require that A proposed maintenance is provided plan to ensure the flood-carrying capacity within the altered or relocated portion of said the watercourse so that the flood carrying capacity is not diminished will be maintained; or
- ~~b.~~ Certification by a registered professional engineer that the project has been designed to retain its flood carrying capacity without periodic maintenance.
3. New Technical Data. Notify the Federal Insurance Administration of changes in the special flood hazard area based on new or improved scientific data that more accurately reflect the flood hazard boundaries and water surface elevations. The City will apply to FEMA for a CLOMR prior to permit issuance for:
 - ~~a.~~ Proposed floodway encroachments that will increase the base flood elevation; and
 - ~~b.~~ Proposed development that will increase the base flood elevation by more than 1 foot in areas where FEMA has provided base flood elevations but no floodway (see Subsection 24.50.060 D.)
4. Letter of Map Revision. Require the applicant to notify FEMA within six months of project completion when FEMA has issued a CLOMR for the project. This notification to FEMA must be provided as a Letter of Map Revision (LOMR).

F. Flood hazard areas.

- 1. General.** All new construction and substantial improvements ~~shall~~must be anchored to prevent flotation, collapse or lateral movement of the structure resulting from hydrostatic and hydrodynamic loads and effects of buoyancy.
- 2. Residential construction.**
 - a.** New construction and substantial improvement of any residential structure ~~shall~~must have the lowest floor, including basement, elevated to or above the flood protection elevation. Floodproofing of “lowest floor” space is not permitted.
 - b.** ~~Fully Enclosed~~ areas below the lowest floor that are subject to flooding are ~~prohibited or shall be~~ unless they are used solely for parking of vehicles, building access or limited storage and ~~be~~are designed to automatically equalize hydrostatic flood forces on exterior walls by allowing the entry and exit of floodwaters.

Designs for meeting this requirement must ~~either be certified by a registered professional engineer or architect or~~ must meet or exceed the following minimum criteria:

- ~~(1)~~ There must be a minimum of two openings having an
different sides of each enclosed area;
 - ~~(2)~~ The total net area of not all openings for each enclosed area
must not be less than one square inch for every square foot
of enclosed area subject to flooding shall be provided or be
certified by a registered design professional;
 - ~~(23)~~ The bottom of all openings shallmay be no higher than ~~one~~1
foot above grade;
 - ~~(34)~~ Openings may be equipped with screens, louvers, or other
coverings or devices provided that they permit the automatic
entry and exit of floodwaters-; and
 - ~~(5)~~ An agreement approved by the Floodplain Administrator not
to convert the use of the enclosed area must be recorded
against the property deed when required by the Floodplain
Administrator.
- ~~(a)c.~~ Fills required to elevate the lowest floor to the flood protection level
shallmust comply with Chapter 24.70. Fill selection and placement
shallmust recognize the effects of inundation from floodwaters on
slope stability, fill settlement, and scour. The minimum elevation at
the top of the fill slope ~~shall~~must be at or above the basedesign flood
~~level~~elevation. Minimum distance from any point of the building
perimeter to the top of the fill slope ~~shall~~must be ~~either~~at least 25
feet or twice the depth of fill at that point, whichever is the greater
distance.
- ~~(b)~~ Piling foundations required to elevate the lowest
habitable floor to the flood protection level shall
comply with Section 1809 and 1808 of the Structural
Specialty Code. Pilings shall be spaced no more than
10 feet apart, and reinforcement shall be provided for
piling more than 6 feet above the ground level.
3. Subdivision proposals.
 - a. All subdivision proposals ~~shall~~must be consistent with the need to
minimize flood damage;

securely anchored to prevent flotation, collapse or lateral movement; and ~~shall be installed~~ using methods and practices that minimize flood damage. The construction must conform to the requirements of Subsection 24.50.060 F.2. Anchoring methods may include, but are not limited to, use of over-the-top or frame ties to ground anchors (Refer to FEMA's "Manufactured Home Installation in Flood Hazard Areas" guidebook for additional techniques).

6. Utilities. All new and replacement water supply and ~~replacement~~ sanitary sewage systems ~~shall~~must be designed to minimize or eliminate infiltration of flood-waters into the systems and discharges from the sanitary sewage systems into flood-waters. On-site waste disposal systems ~~shall~~must be located to avoid impairment to them or contamination from them during flooding.
7. Construction materials and methods. All new construction and substantial improvements ~~shall~~must be constructed with materials and utility equipment resistant to flood damage, using methods and practices that minimize flood damage. Electrical, heating, ventilation, plumbing and air-conditioning equipment and other service facilities ~~shall~~must be protected to or above the flood protection elevation.
8. Balanced Cut and Fill Required. In all ~~F~~lood hazard ~~Management Areas~~ of the City not addressed by Subsection 24.50.060 G., balanced cut and fill shall be required. All fill placed at or below the base flood elevation shall be balanced with at least an equal amount of soil material removal. Soil material removal shall be within the same flood hazard area identified in Subsections 24.50.050 A. through I.
 - a. Excavation shall not be counted as compensating for fill if such areas will be filled with water in non-storm winter conditions.
 - b. Temporary fills permitted during construction shall be removed.
9. ~~Tanks anchoring. Tanks containing hazardous materials must be anchored to prevent flotation if they are located in areas of special flood hazard or flood management areas.~~
 - a. Underground tanks must be anchored to prevent flotation, collapse, and lateral movement under conditions of the design flood.
 - b. Above-ground tanks must be installed at or above the flood protection elevation or be anchored to prevent flotation, collapse, and lateral movement under conditions of the design flood.
10. Uncontained hazardous materials as referred to in Section 101 (14) of the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (42 U.S. Section 9601 et seq.) (CERCLA), Ssection 502 (13) of the

Clean Water Act and any other substances so designated by the Director of the Bureau of Development Services are prohibited in flood ~~management~~hazard areas.

11. AH/AO Zone Drainage. Adequate drainage paths shall be provided around structures on slopes to guide floodwaters around and away from proposed structures.

G. Johnson Creek Flood Zones - Special Provisions. In addition to other requirements of this ~~e~~Chapter, the following requirements ~~shall~~ apply within designated portions of the Johnson Creek Flood Zones:

1. All Johnson Creek Flood Zones
 - a. Balanced cut and fill. Within all areas of the Johnson Creek Flood Zones, all new fills below the base flood elevation ~~shall~~must be accompanied by an equal amount of excavation on the same site so that the storage capacity of the floodway and flood fringe is retained.
 - b. Mitigation payment allowed in lieu of balanced cut and fill. After September 1, 1998 residential properties within the area of the 100 year floodplain, but outside of the floodway and Flood Risk Area, and bounded by I-205 on the west, SE 142nd Avenue on the east, and the Springwater Corridor Trail on the south, may elect to pay into the Johnson Creek Fill Mitigation Bank in lieu of creating a balanced cut and fill. The amount of the payment ~~shall~~will be determined by the Bureau of Environmental Services.
2. Johnson Creek Flood Risk Area. The following provisions ~~shall~~ apply within the Johnson Creek Flood Risk Area, as established in Chapter 33.537~~535~~ of the City Code:
 - a. Balanced cut and fill. The requirements of ~~s~~Subsection G.1. above, ~~shall~~ apply within the Johnson Creek Flood Risk Area.
 - b. Reduction in flooding capacity prohibited. Structures, fill or other development ~~shall~~are only ~~be~~ allowed in the Johnson Creek Flood Risk Area when they are designed so that there ~~is~~will be no significant reduction in the storage capacity of the floodway and floodway fringe and there ~~is~~will be no significant impediment to the passage of flood-waters.
 - c. Exceptions to the applicability of Subsection 24.50.060 G.2.:
 - (1) One-story, detached accessory buildings used as tool and storage sheds, playhouses ~~and~~or similar uses, provided the floor area does not exceed 120 square feet.

- (2) Parking garages accessory to one- and two-family structures, provided the floor area does not exceed 300 square feet.
 - (3) Fences ~~which~~that do not prevent the flow of water.
- d. Buildings designed to meet all of the following criteria ~~shall~~will be presumed to comply with Subsection 24.50.060-G.2.:
- (1) At least 50 percent of perimeter walls located at, or below, the base flood elevation ~~shall~~will remain open and unenclosed;
 - (2) At least 25 percent of each perimeter wall located at, or below, the base flood elevation ~~shall~~will remain open and unenclosed; and
 - (3) The footprint of all portions of the building located at, or below, the base flood elevation ~~shall~~may not exceed 15 percent of the footprint of the building located above the base flood elevation.

24.50.065 Recreational Vehicles located in Areas of Special Flood Hazard or Base Flood Zones.

- A. Any recreational vehicle placed on a site located in either an ~~A~~Special ~~F~~Hazard or in the base flood zone ~~shall~~must:
1. Meet the elevation and anchoring requirements for manufactured homes;
 2. Be on the site for fewer than 180 consecutive days; or
 3. Be fully licensed and ready for highway use. As used in this Section, “ready for highway use” means that the vehicle is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and has no permanently attached additions.
- B. For the purpose of this Section, “recreational vehicle” means any vehicle which is:
1. Built on a single chassis;
 2. 400 square feet or less when measured at the largest horizontal projection;
 3. Designed to be self-propelled or permanently towable by a light duty truck; and
 4. Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel or seasonal use.

24.50.070 Appeals and Variances.

- A.** Appeals. Any person aggrieved by a requirement, decision, or determination made pursuant to the administration of this Chapter may appeal such ~~action~~ requirement, decision, or determination to the BDS Administrative Appeal Building Board of Appeal in accord with Chapter 24.10.
- B.** Variances. If variances from requirements of this Chapter are requested, all relevant factors and standards specified in ~~other sections of this Chapter shall~~ will be considered, as well as the following:
1. The danger that materials may be swept into other lands to the injury of others;
 2. The danger to life and property due to flooding or erosion damage;
 3. The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner;
 4. The importance of the services provided by the proposed facility to the ~~community~~ City;
 5. The necessity to the facility of a waterfront location, where applicable;
 6. The availability of alternative locations, not subject to flooding or erosion damage;
 7. The compatibility of the proposed use with existing anticipated development;
 8. The relationship of the proposed use to the Comprehensive Plan and Floodplain Management Program for that area;
 9. The safety of access to the property in times of flood for ordinary and emergency vehicles;
 10. The expected heights, velocity, duration, rate of rise, and sediment transport of the flood-waters and the effects of wave action, if applicable, expected at the site;
 11. The costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical, and water systems, and streets and bridges; ~~Upon consideration of the factors listed above and the purposes of this Chapter, such conditions may be attached to the granting of variances as deemed necessary.~~
- C.** Conditions for variances. Upon consideration of the factors listed above and the


purposes of this Chapter, such conditions may be attached to the granting of variances as are deemed necessary.

1. Generally, the only condition under which a variance from the elevation standard may be issued is for new construction and substantial improvements to be erected on a lot of 1/2 acre or less in size contiguous to and surrounded by lots with existing structures constructed below the base flood level, ~~providing the items (1-11) in Subsection 24.50.070 B.~~ have been fully considered. As the lot size increases, the technical justification required for issuing the variance increases.
2. Variances ~~shall~~will not be issued within a designated floodway if any increase in flood levels during the base flood discharge would result.
- ~~3. Variances may be issued for the reconstruction, rehabilitation or restoration of structures listed on the National Register of Historic Places or the State Inventory of Historic Places, without regard to the procedures set forth in this Section.~~
43. Variances ~~shall~~will only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
54. Variances ~~shall~~will only be issued upon:
 - a. A showing of good and sufficient cause;
 - b. A determination that failure to grant the variance would result in exceptional hardship to the applicant; and
 - c. A determination that the granting of a variance would not result in increased flood heights, additional threats to public safety, extraordinary public expense, ~~creating a~~causing a nuisance, ~~causing~~causing fraud on or victimization of the public, or creating a conflict with existing local laws or ordinances.
65. Any applicant to whom a variance is granted ~~shall~~will be given written notice that the structure will be permitted to be built with a lowest floor elevation below the base flood elevation and that the cost of flood insurance will be commensurate with the increased risk resulting from the reduced lowest floor elevation as applicable.
76. Variances as interpreted in the National Flood Insurance Program are based on the general zoning law principle in that they pertain to a physical piece of property; ~~they~~ Variances are not personal in nature and do not pertain to the structure, its inhabitants, or economic or financial circumstances. ~~They primarily address small lots in densely populated residential neighborhoods.~~ As such, variances from the flood elevations should be quite rare.

- 87.** Variances may be issued for nonresidential buildings in very limited circumstances to allow a lesser degree of floodproofing than watertight or dry-floodproofing, where it can be determined that such action will have low damage potential; complies with all other variance criteria, except Subsection 24.50.070 C.1. and otherwise complies with Subsections 24.50.060 F.1. and 24.50.060 F.7.

Repeal: Title 24 Figure 1 Basic Floodplain Relationships

BASIC FLOODPLAIN RELATIONSHIPS



CHAPTER 24.10 - ADMINISTRATION AND ENFORCEMENT

Amend Section 24.10.072 Other Structures and Construction Activities.

A. Regulated structures and construction activities. The provisions of this Title apply to the following structures and construction activities regardless of when a permit was applied for or approved:

A.1. – A.19. – No changes.

20. Structures located within flood hazard areas as defined in Chapter 24.50, regardless of whether such structures are exempt under the State of Oregon Residential Specialty Code or Structural Specialty Code.

(Remainder of Section is unchanged)