Table 1 Recommended Private Right-of-Way Tract Widths (feet)

Setback	Curb	Paving	Curb	Planter Strip	Sidewalk	Setback	ROW Width
Streets less t	han 300 feet lo	ng serving less	than 4 lots (N	o sidewalk req	uired)		
1	1	18*	1	0	0	1	22
Must be poste	ed "No Parking"	both sides		•			
Streets less t	han 300 feet lo	ng serving 4 lo	ts or more (Si	dewalk require	ed on one side o	of street)	
1	0.5	20	0.5	0	5	1	28
1	0.5	20	0.5	4	5	1	32
Must be poste	ed "No Parking"	' both sides					
Streets less t	han 300 feet lo	ng serving 4 lo	ts or more (Si	dewalk require	ed on one side o	of street)	
1	0.5	26	0.5	0	5	1	34
1	0.5	26	0.5	4	5	1	38
One side of st	treet must be po	sted "No Parki	ng''				
Streets 300 f	eet or longer (S	Sidewalk on on	e side of stree	t and turnarou	ınd required)		
1	0.5	28	0.5	0	5	1	36
1	0.5	28	0.5	4	5	1	40
One side of st	treet must be po	sted "No Parki	1g"	•			
	•		C				
1	0.5	32	0.5	0	5	1	40
1	0.5	32	0.5	4	5	1	44
				1			
Parking allow	ed both sides o	f street					
Parking allow	ved both sides o	f street					
		f street					
			1	0	0	1	15
Alleys (One	way traffic)	11*	llev	0	0	1	15
Alleys (One		11*	llley	0	0	1	15

Must be posted "No Parking" both sides of alley

Common Greens

Sidewalk Width (need not be centered in ROW)	Landscape Feature (total width on both sides of sidewalk)	ROW Width	
5	10	15	

22

Pedestrian Connections

- Control Cont					
Setback / Landscape Feature	Sidewalk Width (centered in ROW)	Setback / Landscape Feature	ROW Width		
2	6 (Pedestrian only)	2	10		
1.5	12 (Pedestrian & bicycle)	1.5	15		

^{*} Requires mountable curbs