

IR 3863564



City of Portland, Oregon - Bureau of Development Services

1900 SW Fourth Avenue • Portland, Oregon 97201 | 503-823-7300 | www.portlandoregon.gov/bds



High Efficiency Interior Lighting Systems Form

Permit No.: 16-213506 RS Jurisdiction: Portland

Site Address: 5866 NE Mason Street

Subdivision/Lot: _____ and/or

Map and Tax Lot: 1N2E 190A 7100 Tax Lot No 3

By my signature below, I certify that a minimum of fifty (50) percent of the permanently installed lighting fixtures in the above mentioned building have been installed with high efficiency lamps, including compact or linear fluorescent lamps. (Oregon Residential Specialty Code N1107.2⁽¹⁾)

Signature: [Signature] Date: 7/13/18
Owner/General Contractor/Authorized Agent

Print Name: Thomas Custello

⁽¹⁾ORSC Section N1107.2. High-efficiency interior lighting systems. A minimum of fifty (50) percent of the permanently installed lighting fixtures shall be installed with compact or linear fluorescent, or a lighting source that has a minimum efficacy of 40 lumens per input watt. Screw-in compact fluorescent lamps comply with this requirement.

The building official shall be notified in writing at the final inspection that a minimum of fifty percent of the permanently installed lighting fixtures contain high-efficacy lamps. Screw-in compact fluorescent lamps comply with this requirement.

insp_moistcontent_efflight 8/16/17

tear at perforation



City of Portland, Oregon - Bureau of Development Services

1900 SW Fourth Avenue • Portland, Oregon 97201 | 503-823-7300 | www.portlandoregon.gov/bds



Moisture Sensitive Wood Framing Moisture Content Form

I, _____, am the general contractor or the owner/builder at the following address:

Street Address _____

City _____ State _____ Zip Code _____

Permit No.: _____ Jurisdiction: _____

Subdivision/Lot: _____ and/or Map and Tax Lot: _____

To conform with the 2014 Oregon Residential Specialty Code (ORSC), Section R318.2, I am notifying the building official that I am aware of the moisture content requirement of ORSC Section R318.2 and have taken steps to meet this code requirements.


Section R318.2 Moisture Content. Prior to issuance of the insulation/vapor barrier approval required by R109.1.5.2 of this code.

(A) All moisture-sensitive wood framing members used in construction shall have a moisture content of not more than 19 percent of the weight of dry wood framing members.

(B) The general contractor or the owner who was issued the structural permit shall notify the building official on a division approved form that the contractor or the owner who was issued the structural permit is aware of and has taken steps to meet the requirement in paragraph (A).

Signature: _____ Date: _____
Owner/Builder/General Contractor/Authorized Agent

insp_moistcontent_efflight 8/16/17



Unit B-2
5866 NE Mason St
IUR 3863564

14255 S.W. Galbreath Dr., Sherwood, OR
Phone (503) 625-9700~Fax (503) 625-9730

Certificate of Insulation

Contractor: ORANGE SPLOT, LLC

Job Name: BLDG B - B-1, B-2, B-3, B-4

Job Address: 5862, 5866, 5870, 5874 NE MASON ST

City: PORTLAND

State: OR

Job Number: JB-44157

Customer ID: ORA100

Contractors Telephone: 503-288-8318

Proposal Number: BD-44157

Permit Number:

Product	Location
Flame spread poly	tented at attic sprinkler pipes
Labor difference for areas requiring drill	and fill
Loose fill cellulose	R-49 in attic over living space
Attempt to install and foam Thermal Ply	after showers are set
Foam around	cans, bath fans, kitchen fans
THERMAL PLY 4X8	install and foam Thermal Ply after showers are set
Loose fill cellulose	dense pack 2X8 cell w/netting - exterior wall
Loose fill cellulose	dense pack 2x4 cell w/netting - party wall
R-21 unfaced batts	at rim joists
FSK Facing	at rim joists
Baffles	at eave vents
Foam No Expand Window & Door	Polycel / Chink
Air	sealant package
Caulk	plates 2 story
SILL SEAL 3.5X50	Sealer
R-38 unfaced batts	at flat ceilings
R-11 unfaced batt	at flat ceilings (Added to R-38 to equal R-49)
Picture frame foam sealed	at rim joists
R-38 unfaced batts	at overhangs

THE FOLLOWING PRODUCTS HAVE BEEN INSTALLED AS SPECIFIED ABOVE

	R-Value	Thickness	Bags	Footage
<input type="checkbox"/> CELLULOSE				
<input type="checkbox"/> KNAUF JETSTREAM				
<input type="checkbox"/> OWENS CORNING L77				
<input type="checkbox"/> CERTAINTEED INSULSAFE				
ATTIC OF HOUSE	R-49	14.7		
ATTIC OF GARAGE				

☒ John Magville

Authorized Agent: Handy Johnson Date: 6/28/10

*The higher the R-Value the greater the Insulating Power. Loose fill insulations vary in thermal performance due to factors such as aging, mean temperature, convection, moisture absorption and insulation variation.